# Introductory Physics 141/151/161 Self-Guided Learning Problems



#### 1 Kinematics

- Two Bumper Cars
- Two Bumper Cars-Solution
- 2D Basketball Trajectory
- 2D Basketball Trajectory-Solution

#### 2 Newton's Laws and Force

- Firing a Speargun
- Firing a Speargun-Solution

### 3 Work and Energy

- Loop the Loop
- Loop the Loop-Solution

◆□▶ ◆□▶ ◆ □▶ ◆ □▶ ● □ ● ○ ○ ○ ○

s 141/151/16

### 4 Center of Mass, Momentum, Collisions

- Spring-Driven Collision
- Spring-Driven Collision-Solution

#### **5** 1D Rotation

- Rolling with Slipping
- Rolling with Slipping-Solution

#### 6 Vector Torque, Angular Momentum, and Rotational Collisions

s 141/151/16

- A Bullet Grazes a Sphere
- A Bullet Grazes a Sphere-Solution

### 7 Static Equilibrium

- Carrying A Box Up the Stairs
- Carrying A Box Up the Stairs-Solution

### 8 Fluids

- Draining into a Lake
- Draining into a Lake-Solution

#### Oscillations

- Oscillations: A Rolling Pendulum
- Oscillations: A Rolling Pendulum-Solution

(日)、(型)、(目)、(目)、(目)、(の)、()

s 141/151/16

### 10 Waves on a String

- Construct a Travelling WaveConstruct a Travelling Wave-Solution

#### Sound

- Passed by the Ambulance
- Passed by the Ambulance-Solution

#### 12 Gravitation

- Collision with a Neutron Star
- Collision with a Neutron Star-Solution

◆□▶ ◆□▶ ◆ □▶ ◆ □▶ ● □ ● ○ ○ ○ ○

cs 141/151/161

13 End

## About These Problems

This is an experiment. Beamer allows me to make slides that will successively reveal lines of math-heavy text. This gives me a unique opportunity to build a collection of self-guided learning problems for physics that do what I've fantasized about doing for years now – present a problem, then provide a hint, then another hint, then another (or reveal a step, and then another step) until finally, the entire souution is presented, annotated.

Hopefully these problems will help students everywhere as they struggle to learn physics problems solving techniques and learn to "think like a physicist" as they do so.

To use this resource, pick a problem or topic from the table of contents and go directly to it, or work your way through all the problems systematically. Work on a separate sheet of paper, and when you get stuck, page down through the frames to see (hopefully) where you went wrong.

Remember, the point is to **master these problems**, not just to get through them. Make sure that before you are done, you can do every problem **without looking**, **without hints**, and **without remembering the exact solution** but rather, understanding *how* to find it!



• Two bumper cars are headed straight at one another, one travelling at 2v<sub>0</sub> to the right, the other at speed v<sub>0</sub> to the left. When they are separated by a distance *D*, the car on the right slows down with a constant acceleration a<sub>0</sub>. Does the right hand car manage to stop before being hit by the left hand car?

E 990



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

• Two bumper cars are headed straight at one another, one travelling at 2v<sub>0</sub> to the right, the other at speed v<sub>0</sub> to the left. When they are separated by a distance *D*, the car on the right slows down with a constant acceleration a<sub>0</sub>. Does the right hand car manage to stop before being hit by the left hand car?

2



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

• Two bumper cars are headed straight at one another, one travelling at 2v<sub>0</sub> to the right, the other at speed v<sub>0</sub> to the left. When they are separated by a distance *D*, the car on the right slows down with a constant acceleration a<sub>0</sub>. Does the right hand car manage to stop before being hit by the left hand car?

Solve the equations of motion for  $x_l(t)$ ,  $v_l(t)$ ,  $x_r(t)$ ,  $v_r(t)$  for the left and right hand cars respectively.



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

• Two bumper cars are headed straight at one another, one travelling at 2v<sub>0</sub> to the right, the other at speed v<sub>0</sub> to the left. When they are separated by a distance *D*, the car on the right slows down with a constant acceleration a<sub>0</sub>. Does the right hand car manage to stop before being hit by the left hand car?

∢ ≣⇒

э.

Solve the equations of motion for  $x_l(t)$ ,  $v_l(t)$ ,  $x_r(t)$ ,  $v_r(t)$  for the left and right hand cars respectively. Find the time the car on the right comes to rest,  $t_r$ .



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

• Two bumper cars are headed straight at one another, one travelling at 2v<sub>0</sub> to the right, the other at speed v<sub>0</sub> to the left. When they are separated by a distance *D*, the car on the right slows down with a constant acceleration a<sub>0</sub>. Does the right hand car manage to stop before being hit by the left hand car?

(日) (日) (日)

ъ

Solve the equations of motion for  $x_l(t)$ ,  $v_l(t)$ ,  $x_r(t)$ ,  $v_r(t)$  for the left and right hand cars respectively. Find the time the car on the right comes to rest,  $t_r$ . Evaluate the positions of both cars at that time.



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

• Two bumper cars are headed straight at one another, one travelling at 2v<sub>0</sub> to the right, the other at speed v<sub>0</sub> to the left. When they are separated by a distance *D*, the car on the right slows down with a constant acceleration a<sub>0</sub>. Does the right hand car manage to stop before being hit by the left hand car?

< AP >

⇒

ъ

Solve the equations of motion for  $x_l(t)$ ,  $v_l(t)$ ,  $x_r(t)$ ,  $v_r(t)$  for the left and right hand cars respectively. Find the time the car on the right comes to rest,  $t_r$ . Evaluate the positions of both cars at that time. Have they hit already? If they did hit, could you tell *where* they hit?



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

• Two bumper cars are headed straight at one another, one travelling at 2v<sub>0</sub> to the right, the other at speed v<sub>0</sub> to the left. When they are separated by a distance *D*, the car on the right slows down with a constant acceleration a<sub>0</sub>. Does the right hand car manage to stop before being hit by the left hand car?

э.

Solve the equations of motion for  $x_l(t)$ ,  $v_l(t)$ ,  $x_r(t)$ ,  $v_r(t)$  for the left and right hand cars respectively. Find the time the car on the right comes to rest,  $t_r$ . Evaluate the positions of both cars at that time. Have they hit already? If they did hit, could you tell *where* they hit?

 $\ast$  - The solution is on the next page. Don't advance until you are ready!

Kinematics:	Two Bump	er Cars-Solution
		Solution: $x_l(t) = 2v_0 t$ , $v_l(t) = 2v_0$
D	x	$x_r(t) = D - v_0 t + \frac{1}{2}a_0 t^2,  v_r(t) = -v_0 + a_0 t$

<=><=><=><=><=>のへの

< (F) >

141/151/161

Solution: 
$$x_l(t) = 2v_0 t$$
,  $v_l(t) = 2v_0$   
 $x_r(t) = D - v_0 t + \frac{1}{2}a_0 t^2$ ,  $v_r(t) = -v_0 + a_0 t$   
Find the time:  $t_r = \frac{v_0}{a_0}$ .

s 141/151

Solution: 
$$x_{l}(t) = 2v_{0}t$$
,  $v_{l}(t) = 2v_{0}$   
 $x_{r}(t) = D - v_{0}t + \frac{1}{2}a_{0}t^{2}$ ,  $v_{r}(t) = -v_{0} + a_{0}t$   
Find the time:  $t_{r} = \frac{v_{0}}{a_{0}}$ . The left hand car is then at  $x_{l}(t_{r}) = \frac{2v_{0}^{2}}{a_{0}}$  and the right hand car is at  $x_{r}(t_{r}) = D - \frac{v_{0}^{2}}{a_{0}} + \frac{v_{0}^{2}}{2a_{0}} = D - \frac{v_{0}^{2}}{2a_{0}}$ .

s 141/151

・ロト・1日ト・1日ト・日 うへで

Find the time: 
$$t_r = \frac{v_0}{a_0}$$
. The left hand car is then at  $x_l(t) = 2v_0 t$ ,  $v_l(t) = 2v_0$   
hand car is at  $x_r(t_r) = D - \frac{v_0^2}{a_0} + \frac{v_0^2}{2a_0} = D - \frac{v_0^2}{2a_0}$ . If  $D - \frac{v_0^2}{2a_0} < \frac{2v_0^2}{a_0}$  they will collide before the right hand car comes to rest. We can simplify this to:

$$D < \frac{5v_0^2}{2a_0}$$

Physics 141/151/161

・ロト・1日ト・1日ト・日 うへで

G B

Find the time: 
$$t_r = \frac{v_0}{a_0}$$
. The left hand car is then at  $x_l(t) = 2v_0 t$ ,  $v_l(t) = 2v_0$   
hand car is at  $x_r(t_r) = D - \frac{v_0^2}{a_0} + \frac{v_0^2}{2a_0} = D - \frac{v_0^2}{2a_0}$ . If  $D - \frac{v_0^2}{2a_0} < \frac{2v_0^2}{a_0}$  they will collide before the right hand car comes to rest. We can simplify this to:

$$D < \frac{5v_0^2}{2a_0}$$

It makes sense – larger D makes it *less* likely to collide, larger  $a_0$  makes it *less* likely they will collide, larger  $v_0$  makes it *more* likely.

ics 141/151/161

Solution: 
$$x_l(t) = 2v_0 t$$
,  $v_l(t) = 2v_0$   
 $x_r(t) = D - v_0 t + \frac{1}{2}a_0 t^2$ ,  $v_r(t) = -v_0 + a_0 t$ 

Find the time:  $t_r = \frac{v_0}{a_0}$ . The left hand car is then at  $x_l(t_r) = \frac{2v_0^2}{a_0}$  and the right hand car is at  $x_r(t_r) = D - \frac{v_0^2}{a_0} + \frac{v_0^2}{2a_0} = D - \frac{v_0^2}{2a_0}$ . If  $D - \frac{v_0^2}{2a_0} < \frac{2v_0^2}{a_0}$  they will collide before the right hand car comes to rest. We can simplify this to:

$$D < \frac{5v_0^2}{2a_0}$$

It makes sense – larger D makes it *less* likely to collide, larger  $a_0$  makes it *less* likely they will collide, larger  $v_0$  makes it *more* likely. Knowing they collide, if we write:

$$x_l(t_c) = 2v_0t_c = D - v_0t_c + \frac{1}{2}a_0t_c^2 = x_r(t_c)$$

would let us find the time of collision and answer other questions about e.g. their relative velocity at that time. This is a simple quadratic equation for  $t_c$ .

E 990



• A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle  $\theta$  with respect to the horizontal.

(日本)(日本)(日本)

Find  $v_0$ , the **speed** he must release the basketball with (in terms of *H*, *R*, *g* and  $\theta$ ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed  $v_0$  and that the acceleration of the basketball is  $\vec{a} = -g\hat{j}$ , ignoring drag.



 A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

▲■▶▲■▶▲■▶ ■ のへの

Find  $v_0$ , the **speed** he must release the basketball with (in terms of *H*, *R*, *g* and  $\theta$ ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed  $v_0$  and that the acceleration of the basketball is  $\vec{a} = -g\hat{j}$ , ignoring drag.

Hints: First write down  $a_x = 0$ ,  $a_y = -g$  and solve for x(t),  $v_x(t)$ , y(t) and  $v_y(t)$ .



 A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find  $v_0$ , the **speed** he must release the basketball with (in terms of *H*, *R*, *g* and  $\theta$ ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed  $v_0$  and that the acceleration of the basketball is  $\vec{a} = -g\hat{j}$ , ignoring drag.

Hints: First write down  $a_x = 0$ ,  $a_y = -g$  and solve for x(t),  $v_x(t)$ , y(t) and  $v_y(t)$ . Note that there are really two unknowns  $-v_0$  and  $t_b$ , the time the ball reaches the basket.



 A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find  $v_0$ , the **speed** he must release the basketball with (in terms of *H*, *R*, *g* and  $\theta$ ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed  $v_0$  and that the acceleration of the basketball is  $\vec{a} = -g\hat{j}$ , ignoring drag.

Hints: First write down  $a_x = 0$ ,  $a_y = -g$  and solve for x(t),  $v_x(t)$ , y(t) and  $v_y(t)$ . Note that there are really two unknowns  $-v_0$  and  $t_b$ , the time the ball reaches the basket. In order to go through the basket,  $x(t_b) = R$  at the same time that  $y(t_b) = -H$ .



 A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

< 3 b

Find  $v_0$ , the **speed** he must release the basketball with (in terms of *H*, *R*, *g* and  $\theta$ ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed  $v_0$  and that the acceleration of the basketball is  $\vec{a} = -g\hat{j}$ , ignoring drag.

Hints: First write down  $a_x = 0$ ,  $a_y = -g$  and solve for x(t),  $v_x(t)$ , y(t) and  $v_y(t)$ . Note that there are really two unknowns  $-v_0$  and  $t_b$ , the time the ball reaches the basket. In order to go through the basket,  $x(t_b) = R$  at the same time that  $y(t_b) = -H$ . Find  $t_b$  in terms of  $v_0$  and the givens from the x equation.



 A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find  $v_0$ , the **speed** he must release the basketball with (in terms of *H*, *R*, *g* and  $\theta$ ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed  $v_0$  and that the acceleration of the basketball is  $\vec{a} = -g\hat{j}$ , ignoring drag.

Hints: First write down  $a_x = 0$ ,  $a_y = -g$  and solve for x(t),  $v_x(t)$ , y(t) and  $v_y(t)$ . Note that there are really two unknowns  $-v_0$  and  $t_b$ , the time the ball reaches the basket. In order to go through the basket,  $x(t_b) = R$  at the same time that  $y(t_b) = -H$ . Find  $t_b$  in terms of  $v_0$  and the givens from the x equation. Substitute it into the  $y(t_b)$  equation.



 A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find  $v_0$ , the **speed** he must release the basketball with (in terms of *H*, *R*, *g* and  $\theta$ ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed  $v_0$  and that the acceleration of the basketball is  $\vec{a} = -g\hat{j}$ , ignoring drag.

Hints: First write down  $a_x = 0$ ,  $a_y = -g$  and solve for x(t),  $v_x(t)$ , y(t) and  $v_y(t)$ . Note that there are really two unknowns  $-v_0$  and  $t_b$ , the time the ball reaches the basket. In order to go through the basket,  $x(t_b) = R$  at the same time that  $y(t_b) = -H$ . Find  $t_b$  in terms of  $v_0$  and the givens from the x equation. Substitute it into the  $y(t_b)$  equation. Solve for  $v_0$ . There is some algebra involved!



 A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

( ))

Find  $v_0$ , the **speed** he must release the basketball with (in terms of *H*, *R*, *g* and  $\theta$ ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed  $v_0$  and that the acceleration of the basketball is  $\vec{a} = -g\hat{j}$ , ignoring drag.

Hints: First write down  $a_x = 0$ ,  $a_y = -g$  and solve for x(t),  $v_x(t)$ , y(t) and  $v_y(t)$ . Note that there are really two unknowns –  $v_0$  and  $t_b$ , the time the ball reaches the basket. In order to go through the basket,  $x(t_b) = R$  at the same time that  $y(t_b) = -H$ . Find  $t_b$  in terms of  $v_0$  and the givens from the x equation. Substitute it into the  $y(t_b)$  equation. Solve for  $v_0$ . There is some algebra involved!

\* - The solution is on the next page. Don't advance until you are ready!

Initial Conditions:

 $a_x=0, v_{0x}=v_0\cos\theta, x_0=0 \text{ and } a_y=-g, v_{0y}=v_0\sin\theta, y_0=0$ 

s 141/151/

Initial Conditions:

$$a_x = 0, v_{0x} = v_0 \cos \theta, x_0 = 0 \text{ and } a_y = -g, v_{0y} = v_0 \sin \theta, y_0 = 0$$

Integrate:

$$x(t) = v_0 \cos \theta t \quad v_x(t) = v_0 \cos \theta \quad y(t) = -\frac{1}{2}gt^2 + v_0 \sin \theta t \quad v_y(t) = v_0 \sin \theta - gt$$

y Physics 141/151/161

4日 + 4日 + 4目 + 4目 + 1日 - 900

Initial Conditions:

 $a_x = 0, v_{0x} = v_0 \cos \theta, x_0 = 0 \text{ and } a_y = -g, v_{0y} = v_0 \sin \theta, y_0 = 0$ 

Integrate:

 $x(t) = v_0 \cos \theta t \quad v_x(t) = v_0 \cos \theta \quad y(t) = -\frac{1}{2}gt^2 + v_0 \sin \theta t \quad v_y(t) = v_0 \sin \theta - gt$ 

Find the *time*  $t_b$  that the basketball reaches the horizontal position of the hoop:

s 141/151/16

・ロト・団ト・ミト・ミト ヨーのへの

Initial Conditions:

 $a_x=0, v_{0x}=v_0\cos\theta, x_0=0 \text{ and } a_y=-g, v_{0y}=v_0\sin\theta, y_0=0$ 

Integrate:

 $x(t) = v_0 \cos \theta t \quad v_x(t) = v_0 \cos \theta \quad y(t) = -\frac{1}{2}gt^2 + v_0 \sin \theta t \quad v_y(t) = v_0 \sin \theta - gt$ 

Find the *time*  $t_b$  that the basketball reaches the horizontal position of the hoop:

 $R = v_0 \cos \theta t_b \Rightarrow t_b = R/(v_0 \cos \theta)$ 

s 141/151/16

< ロ > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > <

This must also be the time that the ball has exactly the height of the hoop:

Initial Conditions:

 $a_x=0, v_{0x}=v_0\cos\theta, x_0=0 \text{ and } a_y=-g, v_{0y}=v_0\sin\theta, y_0=0$ 

Integrate:

 $x(t) = v_0 \cos \theta t \quad v_x(t) = v_0 \cos \theta \quad y(t) = -\frac{1}{2}gt^2 + v_0 \sin \theta t \quad v_y(t) = v_0 \sin \theta - gt$ 

Find the *time*  $t_b$  that the basketball reaches the horizontal position of the hoop:

$$R = v_0 \cos \theta t_b \Rightarrow t_b = R/(v_0 \cos \theta)$$

This must also be the time that the ball has exactly the height of the hoop:

$$-H = -\frac{1}{2}gt_b^2 + v_0\sin\theta t_b \Rightarrow \frac{gR^2}{2v_0^2\cos^2\theta} = R\tan\theta + H$$

s 141/151/16

▲御▶▲臣▶▲臣▶ 臣 のへの

And finally, we solve for  $v_0$ :

Initial Conditions:

$$a_x = 0, v_{0x} = v_0 \cos \theta, x_0 = 0 \text{ and } a_y = -g, v_{0y} = v_0 \sin \theta, y_0 = 0$$

Integrate:

 $x(t) = v_0 \cos \theta t \quad v_x(t) = v_0 \cos \theta \quad y(t) = -\frac{1}{2}gt^2 + v_0 \sin \theta t \quad v_y(t) = v_0 \sin \theta - gt$ 

Find the *time*  $t_b$  that the basketball reaches the horizontal position of the hoop:

$$R = v_0 \cos \theta t_b \Rightarrow t_b = R/(v_0 \cos \theta)$$

This must also be the time that the ball has exactly the height of the hoop:

$$-H = -\frac{1}{2}gt_b^2 + v_0\sin\theta t_b \Rightarrow \frac{gR^2}{2v_0^2\cos^2\theta} = R\tan\theta + H$$

And finally, we solve for  $v_0$ :

$$v_0 = \sqrt{\frac{gR^2}{2(R\sin\theta\cos\theta + H\cos^2\theta)}}$$

After doing the algebra, check the dimensions. Are they OK?

# Firing a Speargun



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

▲□ ▶ ▲ □ ▶ ▲ □ ▶ □ ● ● ● ●

Hints:

# Firing a Speargun

Hints:



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

・ 型 ト \* 三 ト \* 三 ト 三 ・ つ へ ()

First, draw a picture of the general motion and drag force.

# Firing a Speargun

Hints:



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

< ロ > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < 回 > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > <

First, draw a picture of the *general* motion and drag force. Then, write *Newton's* Second Law, expressing a in terms of v, not x.
Hints:



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

< ≣⇒

э.

< (17) >

First, draw a picture of the *general* motion and drag force. Then, write *Newton's* Second Law, expressing a in terms of v, not x. Then, integrate to find v(t)! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

< 3 >

< AD )

ъ.

#### Hints:

First, draw a picture of the *general* motion and drag force. Then, write *Newton's* Second Law, expressing a in terms of v, not x. Then, integrate to find v(t)! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and  $v = \frac{dx}{dt}!$ 



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

4 ∃⇒

< (C) >

3

Hints:

First, draw a picture of the *general* motion and drag force. Then, write *Newton's* Second Law, expressing a in terms of v, not x. Then, integrate to find v(t)! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and  $v = \frac{dx}{dt}!$  It will come to rest "at"  $t \to \infty$ .



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

4 ∃⇒

< AD )

э.

Hints:

First, draw a picture of the *general* motion and drag force. Then, write *Newton's* Second Law, expressing a in terms of v, not x. Then, integrate to find v(t)! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and  $v = \frac{dx}{dt}$ ! It will come to rest "at"  $t \to \infty$ . So, the range should be the integral of the velocity from 0 to infinity!



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

э

Hints:

First, draw a picture of the *general* motion and drag force. Then, write *Newton's* Second Law, expressing a in terms of v, not x. Then, integrate to find v(t)! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and  $v = \frac{dx}{dt}$ ! It will come to rest "at"  $t \to \infty$ . So, the range should be the integral of the velocity from 0 to infinity!

Note that it will come *almost* to rest (and in the real world, completely to rest) long before t equals "infinity". Note also that the "terminal velocity" in this problem is *zero* as drag is the only force acting.



• An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed  $v_0$  and experiences a *linear* drag force  $F_d = -bv$ opposite to its velocity. Find v(t) and R, the maximum range of the spear.

ъ

Hints:

First, draw a picture of the *general* motion and drag force. Then, write *Newton's* Second Law, expressing a in terms of v, not x. Then, integrate to find v(t)! This involves separating variables and integrating both sides separately, using (easiest) definite integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and  $v = \frac{dx}{dt}$ ! It will come to rest "at"  $t \to \infty$ . So, the range should be the integral of the velocity from 0 to infinity!

Note that it will come *almost* to rest (and in the real world, completely to rest) long before t equals "infinity". Note also that the "terminal velocity" in this problem is *zero* as drag is the only force acting.



R

Physics 141/151/161 G. B

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow$$

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$

cs 141/151/16

・ロト・4回ト・4回ト・4回ト・4日・

R

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$

ics 141/151/161

・ロ・・ 中・ ・ 中・ ・ 日・ ・ 日・

Roh

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$
$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow$$

ics 141/151/161

・ロ・・ 中下・ キャー・ キャー・

12

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$
$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow e^{\left\{\ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t\right\}} \Rightarrow$$

cs 141/151/16

・ロト・4回ト・4回ト・4回ト・4日・

Robert G F

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$
$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow e^{\left\{\ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t\right\}} \Rightarrow \frac{v}{v_0} = e^{-\frac{b}{m}t} \Rightarrow$$

Physics 141/151/161

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

12

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$
$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow e^{\left\{\ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t\right\}} \Rightarrow \frac{v}{v_0} = e^{-\frac{b}{m}t} \Rightarrow \boxed{v(t) = v_0e^{-\frac{b}{m}t}}$$

cs 141/151/16

・ロト・4回ト・4回ト・4回ト・4日・

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$
$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow e^{\left\{\ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t\right\}} \Rightarrow \frac{v}{v_0} = e^{-\frac{b}{m}t} \Rightarrow \boxed{v(t) = v_0e^{-\frac{b}{m}t}}$$
$$\frac{dx}{dt} = v_0e^{-\frac{b}{m}t} \Rightarrow$$

s 141/151/16

・ロト・4回ト・4回ト・4回ト・4日・

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$
$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow e^{\left\{\ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t\right\}} \Rightarrow \frac{v}{v_0} = e^{-\frac{b}{m}t} \Rightarrow \frac{v(t) = v_0e^{-\frac{b}{m}t}}{v_0}$$
$$\frac{dx}{dt} = v_0e^{-\frac{b}{m}t} \Rightarrow x(t) = \int_0^x dx = \int_0^t v_0e^{-\frac{b}{m}t}dt = -\frac{mv_0}{b}\int_0^t e^{-\frac{b}{m}t}\left(-\frac{b}{m}\right)dt$$

cs 141/151/16

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$
$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow e^{\left\{\ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t\right\}} \Rightarrow \frac{v}{v_0} = e^{-\frac{b}{m}t} \Rightarrow \boxed{v(t) = v_0e^{-\frac{b}{m}t}}$$
$$\frac{dx}{dt} = v_0e^{-\frac{b}{m}t} \Rightarrow x(t) = \int_0^x dx = \int_0^t v_0e^{-\frac{b}{m}t}dt = -\frac{mv_0}{b}\int_0^t e^{-\frac{b}{m}t}\left(-\frac{b}{m}\right)dt$$
$$x(t) = \frac{mv_0}{b}\int_{-bt/m}^0 e^u du = \frac{mv_0}{b}\left(1 - e^{-\frac{b}{m}t}\right)$$

ory Physics 141/151/161

so the range R is:

R

$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$
$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$
$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow e^{\left\{\ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t\right\}} \Rightarrow \frac{v}{v_0} = e^{-\frac{b}{m}t} \Rightarrow \boxed{v(t) = v_0e^{-\frac{b}{m}t}}$$
$$\frac{dx}{dt} = v_0e^{-\frac{b}{m}t} \Rightarrow x(t) = \int_0^x dx = \int_0^t v_0e^{-\frac{b}{m}t}dt = -\frac{mv_0}{b}\int_0^t e^{-\frac{b}{m}t}\left(-\frac{b}{m}\right)dt$$
$$x(t) = \frac{mv_0}{b}\int_{-bt/m}^0 e^u du = \frac{mv_0}{b}\left(1 - e^{-\frac{b}{m}t}\right)$$

so the range R is:

$$R = x(t \to \infty) = \frac{mv_0}{b}$$

s 141/151

< □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < □ > < ○ </li>



Solution Map:

• A block of mass *M* sits at the top of a frictionless hill of height *H* leading to a circular loop-the-loop of radius *R*. Find the minimum height  $H_{\min}$  for which the block *barely* gess around the loop staying on the track at the top. If the block is started at this position, what is the normal force exerted by the track at the *bottom* of the loop, where it is greatest?



• A block of mass *M* sits at the top of a frictionless hill of height *H* leading to a circular loop-the-loop of radius *R*. Find the minimum height  $H_{\min}$  for which the block *barely* gess around the loop staying on the track at the top. If the block is started at this position, what is the normal force exerted by the track at the *bottom* of the loop, where it is greatest?

Solution Map: First, draw a force diagram of the mass at the top of the loop (include gravity and the normal force).



• A block of mass *M* sits at the top of a frictionless hill of height *H* leading to a circular loop-the-loop of radius *R*. Find the minimum height  $H_{\min}$  for which the block *barely* gess around the loop staying on the track at the top. If the block is started at this position, what is the normal force exerted by the track at the *bottom* of the loop, where it is greatest?

Solution Map: First, draw a force diagram of the mass at the top of the loop (include gravity and the normal force). Use **conservation of energy** to relate H to v at the top of the loop.



• A block of mass *M* sits at the top of a frictionless hill of height *H* leading to a circular loop-the-loop of radius *R*. Find the minimum height  $H_{\min}$  for which the block *barely* gess around the loop staying on the track at the top. If the block is started at this position, what is the normal force exerted by the track at the *bottom* of the loop, where it is greatest?

э.

Solution Map: First, draw a force diagram of the mass at the top of the loop (include gravity and the normal force). Use **conservation of energy** to relate H to v at the top of the loop. Write N2 for the block at the top of the loop.



• A block of mass *M* sits at the top of a frictionless hill of height *H* leading to a circular loop-the-loop of radius *R*. Find the minimum height  $H_{\min}$  for which the block *barely* gess around the loop staying on the track at the top. If the block is started at this position, what is the normal force exerted by the track at the *bottom* of the loop, where it is greatest?

э.

Solution Map: First, draw a force diagram of the mass at the top of the loop (include gravity and the normal force). Use **conservation of energy** to relate H to v at the top of the loop. Write N2 for the block at the top of the loop. Use centripetal acceleration for a in N2 at the top of the loop.



• A block of mass *M* sits at the top of a frictionless hill of height *H* leading to a circular loop-the-loop of radius *R*. Find the minimum height  $H_{\min}$  for which the block *barely* gess around the loop staying on the track at the top. If the block is started at this position, what is the normal force exerted by the track at the *bottom* of the loop, where it is greatest?

A B > A B > A B >
 A B >
 A
 B >
 A
 B >
 A
 B >
 A
 B >
 A
 B >
 A
 B >
 A
 B >
 A
 B >
 A
 B >
 A
 B >
 A
 B >
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 B
 A
 A
 A

ъ

Solution Map: First, draw a force diagram of the mass at the top of the loop (include gravity and the normal force). Use **conservation of energy** to relate H to v at the top of the loop. Write N2 for the block at the top of the loop. Use centripetal acceleration for a in N2 at the top of the loop. Find  $H_{\min}$  by letting N go to zero and doing algebra.



• A block of mass *M* sits at the top of a frictionless hill of height *H* leading to a circular loop-the-loop of radius *R*. Find the minimum height  $H_{\min}$  for which the block *barely* gess around the loop staying on the track at the top. If the block is started at this position, what is the normal force exerted by the track at the *bottom* of the loop, where it is greatest?

< #**3** →

< 3 h

э

Solution Map: First, draw a force diagram of the mass at the top of the loop (include gravity and the normal force). Use **conservation of energy** to relate H to v at the top of the loop. Write N2 for the block at the top of the loop. Use centripetal acceleration for a in N2 at the top of the loop. Find  $H_{\min}$  by letting N go to zero and doing algebra. Repeat this process for the bottom of the loop, but solve for N at this point.



• A block of mass *M* sits at the top of a frictionless hill of height *H* leading to a circular loop-the-loop of radius *R*. Find the minimum height  $H_{\min}$  for which the block *barely* gess around the loop staying on the track at the top. If the block is started at this position, what is the normal force exerted by the track at the *bottom* of the loop, where it is greatest?

< 3 b

ъ

Solution Map: First, draw a force diagram of the mass at the top of the loop (include gravity and the normal force). Use **conservation of energy** to relate H to v at the top of the loop. Write N2 for the block at the top of the loop. Use centripetal acceleration for a in N2 at the top of the loop. Find  $H_{\min}$  by letting N go to zero and doing algebra. Repeat this process for the bottom of the loop, but solve for N at this point.

 $\ensuremath{^*}$  - The solution is on the next page. Don't advance until you are ready!

R

G. B



v Physics 141/151/161



s 141/151

・ロト・4回ト・4回ト・4回ト・4日・



 ・ < 三 ・ < 三 ・ へ 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < < 回 ・ < 回 ・ < 回 ・ < < 回 ・ < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < 回 ・ < < 回 ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □ ・ < □



・ロット 4回ット 4回ット 4回ット 4回ッ

Robert G. B

At the top: 
$$mgH_{\min} + 0 = mg2R + \frac{1}{2}mv_t^2$$
  
 $mgV_t$   
 $mgH_{\min} = mg2R + \frac{1}{2}mv_t^2 = \frac{1}{2}mgR$   
 $mgH_{\min} = mg2R + \frac{1}{2}mgR \Rightarrow H_{\min} = \frac{5}{2}R$ 

ory Physics 141/151/161

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・



・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

At the top: 
$$mgH_{\min} + 0 = mg2R + \frac{1}{2}mv_t^2$$
  
 $mg_{N_t}$ 
 $mg + M_t = \frac{mv_t^2}{R} \Rightarrow \frac{1}{2}mv_t^2 = \frac{1}{2}mgR$ 
 $mgH_{\min} = mg2R + \frac{1}{2}mgR \Rightarrow H_{\min} = \frac{5}{2}R$ 

ory Physics 141/151/161

At the bottom:

Robert G. B

$$mgH_{\min} + 0 = \frac{5}{2}mgR = \frac{1}{2}mv_b^2$$
 and

At the top: 
$$mgH_{\min} + 0 = mg2R + \frac{1}{2}mv_t^2$$
  
 $mg_{N_t}$ 
 $mg + M_t = \frac{mv_t^2}{R} \Rightarrow \frac{1}{2}mv_t^2 = \frac{1}{2}mgR$ 
 $mgH_{\min} = mg2R + \frac{1}{2}mgR \Rightarrow H_{\min} = \frac{5}{2}R$ 

v Physics 141/151/161

At the bottom:

Robert G

$$mgH_{\min} + 0 = \frac{5}{2}mgR = \frac{1}{2}mv_b^2$$
 and  $N - mg = \frac{mv_b^2}{R} \Rightarrow$ 

At the top: 
$$mgH_{\min} + 0 = mg2R + \frac{1}{2}mv_t^2$$
  
 $mg + \mathcal{M}_t = \frac{mv_t^2}{R} \Rightarrow \frac{1}{2}mv_t^2 = \frac{1}{2}mgR$   
 $mgH_{\min} = mg2R + \frac{1}{2}mgR \Rightarrow H_{\min} = \frac{5}{2}R$ 

At the bottom:

G F

$$mgH_{\min} + 0 = \frac{5}{2}mgR = \frac{1}{2}mv_b^2$$
 and  $N - mg = \frac{mv_b^2}{R} \Rightarrow N = mg + \frac{mv_b^2}{R}$  or:

$$mv_b^2 = 5mg \Rightarrow N = mg + 5mg = 6mg$$

oductory Physics 141/151/161

#### Spring-Driven Collision



In the figure above, a mass 2m connected to a spring k is released from rest when the spring is compressed to the position  $x_0 = -A$  and collides **elastically** with a mass m just as it reaches its equilibrium position moving with velocity  $v_0 \hat{x}$  as shown. Find: A in terms of  $v_0$ , m, and k;  $v_{2m}$  and  $v_m$  immediately after the collision; the maximum amplitude A' of the big (2m) block's oscillation after the collision. Ignore friction, and m starts at rest.


Solution Map: Use energy conservation to find *A*.

In the figure above, a mass 2m connected to a spring k is released from rest when the spring is compressed to the position  $x_0 = -A$  and collides **elastically** with a mass m just as it reaches its equilibrium position moving with velocity  $v_0 \hat{x}$  as shown. Find: A in terms of  $v_0$ , m, and k;  $v_{2m}$  and  $v_m$  immediately after the collision; the maximum amplitude A' of the big (2m) block's oscillation after the collision. Ignore friction, and m starts at rest.

(日本)(日本)

< (17) >



In the figure above, a mass 2m connected to a spring k is released from rest when the spring is compressed to the position  $x_0 = -A$  and collides **elastically** with a mass m just as it reaches its equilibrium position moving with velocity  $v_0 \hat{x}$  as shown. Find: A in terms of  $v_0$ , m, and k;  $v_{2m}$  and  $v_m$  immediately after the collision; the maximum amplitude A' of the big (2m) block's oscillation *after* the collision. Ignore friction, and m starts at rest.

э.

Solution Map: Use energy conservation to find A. Solve the 1D elastic collision for  $v_{2m}$  and  $v_m$ .



In the figure above, a mass 2m connected to a spring k is released from rest when the spring is compressed to the position  $x_0 = -A$  and collides **elastically** with a mass m just as it reaches its equilibrium position moving with velocity  $v_0 \hat{x}$  as shown. Find: A in terms of  $v_0$ , m, and k;  $v_{2m}$  and  $v_m$  immediately after the collision; the maximum amplitude A' of the big (2m) block's oscillation *after* the collision. Ignore friction, and m starts at rest.

э.

Solution Map:

Use energy conservation to find A. Solve the 1D elastic collision for  $v_{2m}$  and  $v_m$ . Use energy conservation again to find A'.



In the figure above, a mass 2m connected to a spring k is released from rest when the spring is compressed to the position  $x_0 = -A$  and collides **elastically** with a mass m just as it reaches its equilibrium position moving with velocity  $v_0 \hat{\mathbf{x}}$  as shown. Find: A in terms of  $v_0$ , m, and k;  $v_{2m}$  and  $v_m$  immediately after the collision; the maximum amplitude A' of the big (2m) block's oscillation *after* the collision. Ignore friction, and m starts at rest.

< 3 b

ъ

#### Solution Map:

Use energy conservation to find A. Solve the 1D elastic collision for  $v_{2m}$  and  $v_m$ . Use energy conservation again to find A'. Pretty simple, but it *mixes* energy conservation and elastic collisions. If you don't remember the solution for the final velocity after a 1D elastic collision, advance the page to see it, but remember that you can't look it up like this on a quiz or exam!



In the figure above, a mass 2m connected to a spring k is released from rest when the spring is compressed to the position  $x_0 = -A$  and collides **elastically** with a mass m just as it reaches its equilibrium position moving with velocity  $v_0 \hat{x}$  as shown. Find: A in terms of  $v_0$ , m, and k;  $v_{2m}$  and  $v_m$  immediately after the collision; the maximum amplitude A' of the big (2m) block's oscillation *after* the collision. Ignore friction, and m starts at rest.

#### Solution Map:

Use energy conservation to find A. Solve the 1D elastic collision for  $v_{2m}$  and  $v_m$ . Use energy conservation again to find A'. Pretty simple, but it *mixes* energy conservation and elastic collisions. If you don't remember the solution for the final velocity after a 1D elastic collision, advance the page to see it, but remember that you can't look it up like this on a quiz or exam!

**1D Elastic Collision Formula:**  $v_f = -v_i + 2v_{cm}$  with  $v_{cm} = \frac{m_1v_{1i} + m_2v_{2i}}{m_1 + m_2}$ 



In the figure above, a mass 2m connected to a spring k is released from rest when the spring is compressed to the position  $x_0 = -A$  and collides **elastically** with a mass m just as it reaches its equilibrium position moving with velocity  $v_0 \hat{x}$  as shown. Find: A in terms of  $v_0$ , m, and k;  $v_{2m}$  and  $v_m$  immediately after the collision; the maximum amplitude A' of the big (2m) block's oscillation *after* the collision. Ignore friction, and m starts at rest.

#### Solution Map:

Use energy conservation to find A. Solve the 1D elastic collision for  $v_{2m}$  and  $v_m$ . Use energy conservation again to find A'. Pretty simple, but it *mixes* energy conservation and elastic collisions. If you don't remember the solution for the final velocity after a 1D elastic collision, advance the page to see it, but remember that you can't look it up like this on a quiz or exam!

**1D Elastic Collision Formula:**  $v_f = -v_i + 2v_{cm}$  with  $v_{cm} = \frac{m_1v_{1i} + m_2v_{2i}}{m_1 + m_2}$ \* - The solution is on the next page. Don't advance until you are ready!



Use mechanical energy conservation before the collision to find A:

$$\frac{1}{2}kA^2 = \frac{1}{2}(2m)v_0^2 \Rightarrow A = \sqrt{\frac{2m}{k}}v_0$$

cs 141/151/16

(日)、(型)、(目)、(目)、(日)、(の)、(の)



Use mechanical energy conservation before the collision to find A:

$$\frac{1}{2}kA^2 = \frac{1}{2}(2m)v_0^2 \Rightarrow A = \sqrt{\frac{2m}{k}}v_0$$

(Note that  $A = \frac{v_0}{\omega}$  as one expects from the solution obtained in Chapter 9.)

cs 141/151/16

(日)、(型)、(目)、(目)、(日)、(の)、(の)



Use mechanical energy conservation before the collision to find A:

$$\frac{1}{2}kA^2 = \frac{1}{2}(2m)v_0^2 \Rightarrow A = \sqrt{\frac{2m}{k}}v_0$$

(Note that  $A = \frac{v_0}{\omega}$  as one expects from the solution obtained in Chapter 9.)

Solve the elastic collision:

$$v_{\rm cm} = \frac{2mv_0}{2m+m} = \frac{2v_0}{3} \Rightarrow \boxed{v_{2m} = \frac{v_0}{3}} \qquad v_m = \frac{4v_0}{3}$$

cs 141/151/16



Use mechanical energy conservation before the collision to find A:

$$\frac{1}{2}kA^2 = \frac{1}{2}(2m)v_0^2 \Rightarrow \boxed{A = \sqrt{\frac{2m}{k}}v_0}$$

(Note that  $A = \frac{v_0}{\omega}$  as one expects from the solution obtained in Chapter 9.)

Solve the elastic collision:

$$v_{\rm cm} = \frac{2mv_0}{2m+m} = \frac{2v_0}{3} \Rightarrow v_{2m} = \frac{v_0}{3} \qquad v_m = \frac{4v_0}{3}$$

Use mechanical energy conservation again to find A':

$$\frac{1}{2}(2m)v_{2m}^2 = \frac{1}{9}mv_0^2 = \frac{1}{2}kA'^2 \Rightarrow \boxed{A' = \sqrt{\frac{2m}{9k}}v_0}$$



• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

▲■▶▲■▶▲■▶ ■ のへの



Solution Map:

• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

(ロ)、(型)、(E)、(E)、(E)、(O)(C)



• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

Solution Map:

As always, draw a force diagram and choose good coordinates. Let  $f_{\rm s}$  and N act at the point of contact.



• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

Solution Map:

As always, draw a force diagram and choose good coordinates. Let  $f_s$  and N act at the point of contact. Next, write N2 for translation and rotation both.



• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

▲■▶▲■▶▲■▶ ■ のへの

Solution Map:

As always, draw a force diagram and choose good coordinates. Let  $f_s$  and N act at the point of contact. Next, write N2 for translation and rotation both. Solve for  $f_s$  (which will **not** contain  $\mu_s$ !).



• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

< 3 b

ъ

#### Solution Map:

As always, draw a force diagram and choose good coordinates. Let  $f_s$  and N act at the point of contact. Next, write N2 for translation and rotation both. Solve for  $f_s$  (which will **not** contain  $\mu_s$ !). You can solve for the acceleration a(t) if you wish as well (this might have been part of the question, and may be needed in order to most easily find  $f_s$ ).



• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

< 3 >

ъ.

#### Solution Map:

As always, draw a force diagram and choose good coordinates. Let  $f_s$  and N act at the point of contact. Next, write N2 for translation and rotation both. Solve for  $f_s$  (which will **not** contain  $\mu_s$ !). You can solve for the acceleration a(t) if you wish as well (this might have been part of the question, and may be needed in order to most easily find  $f_s$ ). Use  $f_s < \mu_s N$  to determine the time that the disk will start to slip.



• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

#### Solution Map:

As always, draw a force diagram and choose good coordinates. Let  $f_s$  and N act at the point of contact. Next, write N2 for translation and rotation both. Solve for  $f_s$  (which will **not** contain  $\mu_s$ !). You can solve for the acceleration a(t) if you wish as well (this might have been part of the question, and may be needed in order to most easily find  $f_s$ ). Use  $f_s < \mu_s N$  to determine the time that the disk will start to slip. If you like, find the *independent* linear and angular accelerations after it starts to slip (this could easily have been a question too).



• A disk with mass M, radius R, is sitting on a rough floor with coefficients of friction  $\mu_{k,s}$  respectively. It is pulled by a force F(t) = At that **increases linearly with time** (A is a constant with units N/sec). Write an expression for  $f_s(t)$ , the **magnitude** of the force of static friction as a function of time. Find the time  $t_s$  that the disk starts to slip instead of roll without slipping.

#### Solution Map:

As always, draw a force diagram and choose good coordinates. Let  $f_s$  and N act at the point of contact. Next, write N2 for translation and rotation both. Solve for  $f_s$  (which will **not** contain  $\mu_s$ !). You can solve for the acceleration a(t) if you wish as well (this might have been part of the question, and may be needed in order to most easily find  $f_s$ ). Use  $f_s < \mu_s N$  to determine the time that the disk will start to slip. If you like, find the *independent* linear and angular accelerations after it starts to slip (this could easily have been a question too).

\* - The solution is on the next page. Don't advance until you are ready!



Choose coordinates so  $a = R\alpha$  (in x-direction). Then:

cs 141/151/16



Choose coordinates so  $a = R\alpha$  (in x-direction). Then:

$$F - f_s = Ma$$
  $au_{in} = f_s R = \frac{1}{2} M R^2 \frac{a}{R}$ 

cs 141/151/16

Choose coordinates so 
$$a = R\alpha$$
 (in x-  
direction). Then:  
 $F - f_s = Ma$   $\tau_{in} = f_s R' = \frac{1}{2}MR^{2'}\frac{a}{R'}$   
Simplify and add:  
 $F = \frac{3}{2}Ma \Rightarrow a = \frac{2F(t)}{3M}, f_s = \frac{1}{3}F(t) = \frac{1}{3}At$ 

cs 141/151/

$$f_{s,k} \xrightarrow{F} \mu_{s,k}$$

Choose coordinates so  $a = R\alpha$  (in x-direction). Then:

$$F - f_s = Ma$$
  $\tau_{\rm in} = f_s R = \frac{1}{2} M R^2 \frac{a}{R}$ 

Simplify and add:

$$F = \frac{3}{2}Ma \Rightarrow a = \frac{2F(t)}{3M}, f_s = \frac{1}{3}F(t) = \frac{1}{3}At$$

(日)、(型)、(目)、(目)、(日)、(の)、(の)

Next, note that  $N - Mg = 0 \Rightarrow N = Mg$  and find the slip time  $t_s$ :

$$f_s = \frac{1}{3}At < \mu_s N = \mu_s Mg \Rightarrow \frac{1}{3}At_s = \mu_s Mg \Rightarrow t_s = \frac{3\mu_s Mg}{A}$$

Physics 141/151/

$$f_{s,k} \xrightarrow{F} Mg \xrightarrow{K} \mu_{s,k}$$

Choose coordinates so  $a = R\alpha$  (in x-direction). Then:

$$F - f_s = Ma$$
  $au_{in} = f_s \mathcal{R} = \frac{1}{2} M \mathcal{R}^2 \frac{a}{\mathcal{R}}$ 

Simplify and add:

$$F = \frac{3}{2}Ma \Rightarrow a = \frac{2F(t)}{3M}, f_s = \frac{1}{3}F(t) = \frac{1}{3}At$$

◆□▶ ◆□▶ ◆ □▶ ◆ □▶ ○ □ ○ ○ ○

Next, note that  $N - Mg = 0 \Rightarrow N = Mg$  and find the slip time  $t_s$ :

$$f_s = \frac{1}{3}At < \mu_s N = \mu_s Mg \Rightarrow \frac{1}{3}At_s = \mu_s Mg \Rightarrow t_s = \frac{3\mu_s Mg}{A}$$

s 141/151

Finally, after it slips,  $f_k = \mu_k Mg$  and hence:

$$f_{s,k} \xrightarrow{F} Mg \xrightarrow{K} \mu_{s,k}$$

Choose coordinates so  $a = R\alpha$  (in x-direction). Then:

$$F - f_s = Ma$$
  $au_{in} = f_s \mathcal{R} = \frac{1}{2} M \mathcal{R}^2 \frac{a}{\mathcal{R}}$ 

Simplify and add:

$$F = \frac{3}{2}Ma \Rightarrow \boxed{a = \frac{2F(t)}{3M}, f_s = \frac{1}{3}F(t) = \frac{1}{3}At}$$

Next, note that  $N - Mg = 0 \Rightarrow N = Mg$  and find the slip time  $t_s$ :

$$f_{s} = \frac{1}{3}At < \mu_{s}N = \mu_{s}Mg \Rightarrow \frac{1}{3}At_{s} = \mu_{s}Mg \Rightarrow t_{s} = \frac{3\mu_{s}Mg}{A}$$

Finally, after it slips,  $f_k = \mu_k Mg$  and hence:

$$F - \mu_k Mg = Ma' \Rightarrow \boxed{a' = \frac{At}{M} - \mu_k g} \quad Rf_k = R\mu_k Mg = \frac{1}{2}MR^2\alpha' \Rightarrow \boxed{\alpha' = \frac{\mu_k g}{R}}$$

s 141/151

Physics 141/151/161

• Note Well:  $a' \neq \alpha' R!$ 

- Note Well:  $a' \neq \alpha' R!$
- We could integrate to find x(t) and v(t) as well, e.g.:

$$v(t) = \int_0^t \frac{2At'}{3M} dt' = \frac{A}{3M} t^2, \quad x(t) = \int_0^t \frac{A}{3M} t'^2 dt' = \frac{A}{9M} t^3 \text{ for } (t \le ts))$$

cs 141/151/16

◆□▶ ◆□▶ ◆ □▶ ◆ □▶ ● □ ● ○ ○ ○ ○

- Note Well:  $a' \neq \alpha' R!$
- We could integrate to find x(t) and v(t) as well, e.g.:

$$v(t) = \int_0^t \frac{2At'}{3M} dt' = \frac{A}{3M} t^2, \quad x(t) = \int_0^t \frac{A}{3M} t'^2 dt' = \frac{A}{9M} t^3 \text{ for } (t \le ts))$$

• For practice, see if you can find v(t) and x(t) for times  $t > t_s$ . Use the result above to find  $x_0$  and  $v_0$  and then integrate a'(t) twice!

s 141/151/16

(日)、(型)、(目)、(目)、(日)、(の)、(の)

- Note Well:  $a' \neq \alpha' R!$
- We could integrate to find x(t) and v(t) as well, e.g.:

$$v(t) = \int_0^t \frac{2At'}{3M} dt' = \frac{A}{3M} t^2, \quad x(t) = \int_0^t \frac{A}{3M} t'^2 dt' = \frac{A}{9M} t^3 \text{ for } (t \le ts))$$

- For practice, see if you can find v(t) and x(t) for times  $t > t_s$ . Use the result above to find  $x_0$  and  $v_0$  and then integrate a'(t) twice!
- Note Well! We can solve for everything using just F for the applied force and substitute F = At only at the end when we need it!

s 141/151/161

- Note Well:  $a' \neq \alpha' R!$
- We could integrate to find x(t) and v(t) as well, e.g.:

$$v(t) = \int_0^t \frac{2At'}{3M} dt' = \frac{A}{3M} t^2, \quad x(t) = \int_0^t \frac{A}{3M} t'^2 dt' = \frac{A}{9M} t^3 \text{ for } (t \le ts))$$

- For practice, see if you can find v(t) and x(t) for times  $t > t_s$ . Use the result above to find  $x_0$  and  $v_0$  and then integrate a'(t) twice!
- Note Well! We can solve for everything using just F for the applied force and substitute F = At only at the end when we need it!

(ロ)、(型)、(E)、(E)、(E)、(O)、(O)

• And note above all that  $f_s = \frac{1}{3}At \neq \mu_s N$ . We only use  $\mu_s N$  to find the (critical) slipping point, never to find  $f_s$  itself!



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

< 3 b

э

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of *m* (relative to *M*) for which this collision is elastic?



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

∢ ≣⇒

ъ

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of m (relative to M) for which this collision is elastic? Solution Map:



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

< 3 b

< A >

ъ

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of m (relative to M) for which this collision is elastic?

Solution Map:

Start by drawing/visualizing the state right after the collision.



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

< (17) >

< 3 b

ъ

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of m (relative to M) for which this collision is elastic?

Solution Map:

Start by drawing/visualizing the state right after the collision. *Both* linear momentum *and* angular momentum are conserved.



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

< 3 )

< A >

ъ

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of m (relative to M) for which this collision is elastic?

Solution Map:

Start by drawing/visualizing the state right after the collision. Both linear momentum and angular momentum are conserved. Use these concepts to find  $v_f$  (to the right) and  $\Omega_f$ .


A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of m (relative to M) for which this collision is elastic?

Solution Map:

Start by drawing/visualizing the state right after the collision. Both linear momentum and angular momentum are conserved. Use these concepts to find  $v_f$  (to the right) and  $\Omega_f$ . Then use  $\Delta E = E_f - E_i$  to find the energy (lost).



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius *R* ( $I = \frac{2}{5}MR^2$ ) grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of m (relative to M) for which this collision is elastic?

Solution Map:

Start by drawing/visualizing the state right after the collision. Both linear momentum and angular momentum are conserved. Use these concepts to find  $v_f$  (to the right) and  $\Omega_f$ . Then use  $\Delta E = E_f - E_i$  to find the energy (lost). Finally, see if any value of *m* will make  $\Delta E = 0$ .



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of m (relative to M) for which this collision is elastic?

Solution Map:

Start by drawing/visualizing the state right after the collision. Both linear momentum and angular momentum are conserved. Use these concepts to find  $v_f$  (to the right) and  $\Omega_f$ . Then use  $\Delta E = E_f - E_i$  to find the energy (lost). Finally, see if any value of *m* will make  $\Delta E = 0$ . Don't forget to give directions! The problem asks for *velocities* which are *vectors!* A picky instructor will take off points if you just give magnitudes!



A small bullet of mass *m* fired at an initial speed of  $v_0$  grazes a free (unpivoted!) sphere sphere of mass *M* and radius  $R (I = \frac{2}{5}MR^2)$  grazes the surface of the sphere at its equator and emerges travelling along the same line at the reduced speed  $v_1 = v_0/2$ .

Find:  $\Omega_f$  the angular velocity of the sphere after the collision; the velocity  $v_f$  of the center of mass of the sphere after the collision; the energy lost during the collision. Is there any value of m (relative to M) for which this collision is elastic?

Solution Map:

Start by drawing/visualizing the state right after the collision. Both linear momentum and angular momentum are conserved. Use these concepts to find  $v_f$  (to the right) and  $\Omega_f$ . Then use  $\Delta E = E_f - E_i$  to find the energy (lost). Finally, see if any value of *m* will make  $\Delta E = 0$ . Don't forget to give directions! The problem asks for *velocities* which are *vectors!* A picky instructor will take off points if you just give magnitudes!



G F

Start by drawing/visualizing the final state of the rotating sphere.

y Physics 141/151/161

・ロト・4回ト・ミト・ミト・ミー・シック



Start by drawing/visualizing the final state of the rotating sphere. ( $v_1 = v_0/2$  and x-directed motion only). Then:

cs 141/151/16



Start by drawing/visualizing the final state of the rotating sphere. ( $v_1 = v_0/2$  and x-directed motion only). Then:

$$p_i = mv_0 = mv_1 + Mv_f = p_f \Rightarrow v_f = \frac{m}{2M}v_0$$

cs 141/151/16



Start by drawing/visualizing the final state of the rotating sphere. ( $v_1 = v_0/2$  and x-directed motion only). Then:

$$p_{i} = mv_{0} = mv_{1} + Mv_{f} = p_{f} \Rightarrow \boxed{v_{f} = \frac{m}{2M}v_{0}}$$
$$L_{i} = mv_{0}R = mv_{1}R + I\Omega_{f} = L_{f} \Rightarrow \boxed{\Omega_{f} = \frac{5mv_{0}}{2M}}$$

$$L_i = mv_0 R = mv_1 R + I\Omega_f = L_f \Rightarrow \Omega_f = \frac{5mv_0}{4MR}$$

ics 141/151/161



Start by drawing/visualizing the final state of the rotating sphere. ( $v_1 = v_0/2$  and x-directed motion only). Then:

$$p_i = mv_0 = mv_1 + Mv_f = p_f \Rightarrow v_f = \frac{m}{2M}v_0$$

$$L_i = mv_0 R = mv_1 R + I\Omega_f = L_f \Rightarrow \Omega_f = \frac{5mv_0}{4MR}$$

Then compute initial and final energies and form  $\Delta E$  (use  ${\cal K}_{\rm rot}=\frac{1}{2}I\Omega_f^2)$ :

s 141/151/16



Start by drawing/visualizing the final state of the rotating sphere. ( $v_1 = v_0/2$  and x-directed motion only). Then:

$$p_i = mv_0 = mv_1 + Mv_f = p_f \Rightarrow v_f = \frac{m}{2M}v_0$$

$$L_{i} = mv_{0}R = mv_{1}R + I\Omega_{f} = L_{f} \Rightarrow \boxed{\Omega_{f} = \frac{5mv_{0}}{4MR}}$$

Then compute initial and final energies and form  $\Delta E$  (use  ${\cal K}_{\rm rot}=\frac{1}{2}I\Omega_f^2)$ :

$$E_{i} = \frac{1}{2}mv_{0}^{2} \qquad E_{f} = \frac{1}{2}m\left(\frac{v_{0}}{2}\right)^{2} + \frac{1}{2}M\left(\frac{mv_{0}}{2M}\right)^{2} + \frac{1}{2}\left(\frac{2}{5}MR^{2}\right)\left(\frac{5mv_{0}}{4MR}\right)^{2}$$
$$\Delta E = \left(\left\{\frac{1}{4} + \frac{7m}{8M}\right\} - 1\right)\frac{1}{2}mv_{0}^{2} \text{ and } \Delta E = 0 \text{ if } \boxed{m = \frac{6}{7}M}$$

s 141/151/16



 Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?

(ロ)、(型)、(E)、(E)、(E)、(O)、(O)



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing  $\phi = \tan^{-1}(h/w)$  in the trig!

(ロ)、(型)、(E)、(E)、(E)、(O)、(O)



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing  $\phi = \tan^{-1}(h/w)$  in the trig!

< ≣⇒

э.

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure.



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing  $\phi = \tan^{-1}(h/w)$  in the trig!

< (17) >

⇒

ъ

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using  $\theta$  only (not  $\phi$ !).



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing  $\phi = \tan^{-1}(h/w)$  in the trig!

< AP >

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using  $\theta$  only (not  $\phi$ !). Can you now write down equations for force balance and torque balance?



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing  $\phi = \tan^{-1}(h/w)$  in the trig!

< 30

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using  $\theta$  only (not  $\phi$ !). Can you now write down equations for force balance and torque balance? Can you solve the torque balance equation for  $F_2$ ?



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing  $\phi = \tan^{-1}(h/w)$  in the trig!

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using  $\theta$  only (not  $\phi$ !). Can you now write down equations for force balance and torque balance? Can you solve the torque balance equation for  $F_2$ ? Can you back substitute to find  $F_1$ ?



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing  $\phi = \tan^{-1}(h/w)$  in the trig!

< 3 b

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using  $\theta$  only (not  $\phi$ !). Can you now write down equations for force balance and torque balance? Can you solve the torque balance equation for  $F_2$ ? Can you back substitute to find  $F_1$ ?



 Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?



 Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?

(ロ)、(型)、(E)、(E)、(E)、(O)、(O)

•  $F_{2x} = F_2 \sin \theta$ ,  $F_{2y} = F_2 \cos \theta$ ,  $F_{gx} = -mg \sin \theta$ ,  $F_{gy} = -mg \cos \theta$ .



 Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?

- $F_{2x} = F_2 \sin \theta$ ,  $F_{2y} = F_2 \cos \theta$ ,  $F_{gx} = -mg \sin \theta$ ,  $F_{gy} = -mg \cos \theta$ .
- (Vertically)  $F_1 + F_2 mg = 0$



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle  $\theta$ . How is the weight distributed between the two workers?
- $F_{2x} = F_2 \sin \theta$ ,  $F_{2y} = F_2 \cos \theta$ ,  $F_{gx} = -mg \sin \theta$ ,  $F_{gy} = -mg \cos \theta$ .
- (Vertically)  $F_1 + F_2 mg = 0$   $\tau_z = wF_2 \cos \theta \frac{mg}{2}(w \cos \theta h \sin \theta) = 0$



 Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?

• 
$$F_{2x} = F_2 \sin \theta$$
,  $F_{2y} = F_2 \cos \theta$ ,  
 $F_{gx} = -mg \sin \theta$ ,  $F_{gy} = -mg \cos \theta$ .  
• (Vertically)  $F_1 + F_2 - mg = 0$ 

• 
$$\tau_z = wF_2\cos\theta - \frac{mg}{2}(w\cos\theta - h\sin\theta) = 0$$

$$F_2 = \frac{mg}{2} \left( 1 - \frac{h}{w} \tan \theta \right) \text{ and } F_1 = \frac{mg}{2} \left( 1 + \frac{h}{w} \tan \theta \right)$$



Note:  $F_1 > F_2$  for all  $\theta \in (0, \pi/2)$ . It's better to be the student at the top!





 Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?

• 
$$F_{2x} = F_2 \sin \theta$$
,  $F_{2y} = F_2 \cos \theta$ ,  
 $F_{gx} = -mg \sin \theta$ ,  $F_{gy} = -mg \cos \theta$ .  
• (Vertically)  $F_1 + F_2 - mg = 0$   
•  $\tau_z = wF_2 \cos \theta - \frac{mg}{2}(w \cos \theta - h \sin \theta) = 0$ 

$$F_2 = \frac{mg}{2} \left( 1 - \frac{h}{w} \tan \theta \right)$$
 and  $F_1 = \frac{mg}{2} \left( 1 + \frac{h}{w} \tan \theta \right)$ 

Note:  $F_1 > F_2$  for all  $\theta \in (0, \pi/2)$ . It's better to be the student at the top! Note:  $F_1 = mg$  when  $\theta = \tan^{-1} \frac{w}{h}$ . At this point  $F_2 = 0$  and the student at the top is just helping balance the load!



• The figure shows a rain-barrel that drains into a nearby lake through an underground pipe. The cross sectional area of the pipe is *a*, the top of the barrel has area  $A \gg a$ , the water has a height *H* in the barrel, and the pipe enters the lake at a depth *D*. Find  $v_p$ , the speed with which the water drains into the lake through the pipe, and the rate of flow through the pipe. Lake and barrel are obviously open to air pressure.



• The figure shows a rain-barrel that drains into a nearby lake through an underground pipe. The cross sectional area of the pipe is *a*, the top of the barrel has area  $A \gg a$ , the water has a height *H* in the barrel, and the pipe enters the lake at a depth *D*. Find  $v_p$ , the speed with which the water drains into the lake through the pipe, and the rate of flow through the pipe. Lake and barrel are obviously open to air pressure.

(ロ)、(型)、(E)、(E)、(E)、(O)、(O)

Pick good coordinates – the y origin at the height of the pipe opening, for example.



• The figure shows a rain-barrel that drains into a nearby lake through an underground pipe. The cross sectional area of the pipe is *a*, the top of the barrel has area  $A \gg a$ , the water has a height *H* in the barrel, and the pipe enters the lake at a depth *D*. Find  $v_p$ , the speed with which the water drains into the lake through the pipe, and the rate of flow through the pipe. Lake and barrel are obviously open to air pressure.

Pick good coordinates – the y origin at the height of the pipe opening, for example. This is a Bernoulli's Formula problem, so start by writing it down.



• The figure shows a rain-barrel that drains into a nearby lake through an underground pipe. The cross sectional area of the pipe is *a*, the top of the barrel has area  $A \gg a$ , the water has a height *H* in the barrel, and the pipe enters the lake at a depth *D*. Find  $v_p$ , the speed with which the water drains into the lake through the pipe, and the rate of flow through the pipe. Lake and barrel are obviously open to air pressure.

▲■▶▲■▶▲■▶ ■ のへの

Pick good coordinates – the y origin at the height of the pipe opening, for example. This is a Bernoulli's Formula problem, so start by writing it down. You'll also need conservation of flow at the top of the barrel and the opening of the pipe.



• The figure shows a rain-barrel that drains into a nearby lake through an underground pipe. The cross sectional area of the pipe is *a*, the top of the barrel has area  $A \gg a$ , the water has a height *H* in the barrel, and the pipe enters the lake at a depth *D*. Find  $v_p$ , the speed with which the water drains into the lake through the pipe, and the rate of flow through the pipe. Lake and barrel are obviously open to air pressure.

< A >

4 ∃ →

ъ

Pick good coordinates – the y origin at the height of the pipe opening, for example. This is a Bernoulli's Formula problem, so start by writing it down. You'll also need conservation of flow at the top of the barrel and the opening of the pipe. The trickiest part of this solution is that you need to use the *static pressure*  $P_p$  at the mouth of the pipe in Bernoulli's Formula, which is not given in the problem.



• The figure shows a rain-barrel that drains into a nearby lake through an underground pipe. The cross sectional area of the pipe is *a*, the top of the barrel has area  $A \gg a$ , the water has a height *H* in the barrel, and the pipe enters the lake at a depth *D*. Find  $v_p$ , the speed with which the water drains into the lake through the pipe, and the rate of flow through the pipe. Lake and barrel are obviously open to air pressure.

ъ

Pick good coordinates – the y origin at the height of the pipe opening, for example. This is a Bernoulli's Formula problem, so start by writing it down. You'll also need conservation of flow at the top of the barrel and the opening of the pipe. The trickiest part of this solution is that you need to use the *static pressure*  $P_p$  at the mouth of the pipe in Bernoulli's Formula, which is not given in the problem. Use the "Torricelli assumption"  $A \gg a$  (really, for the lake side as well) and solve the Bernoulli formula for  $v_p$ !



• The figure shows a rain-barrel that drains into a nearby lake through an underground pipe. The cross sectional area of the pipe is *a*, the top of the barrel has area  $A \gg a$ , the water has a height *H* in the barrel, and the pipe enters the lake at a depth *D*. Find  $v_p$ , the speed with which the water drains into the lake through the pipe, and the rate of flow through the pipe. Lake and barrel are obviously open to air pressure.

< 3 > >

ъ.

Pick good coordinates – the y origin at the height of the pipe opening, for example. This is a Bernoulli's Formula problem, so start by writing it down. You'll also need conservation of flow at the top of the barrel and the opening of the pipe. The trickiest part of this solution is that you need to use the *static pressure*  $P_p$  at the mouth of the pipe in Bernoulli's Formula, which is not given in the problem. Use the "Torricelli assumption"  $A \gg a$  (really, for the lake side as well) and solve the Bernoulli formula for  $v_p$ !



Robert G. B

Choose coordinates like those shown.

ry Physics 141/151/161



Choose coordinates like those shown. Evaluate  $P_{p} = P_{a} + \rho g D$ .

ics 141/151/16

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・



Choose coordinates like those shown. Evaluate  $P_p = P_a + \rho g D$ . Apply Bernoulli Formula:

$$P_{a} + \rho g(H + D) + \frac{1}{2}\rho v_{b}^{2} = P_{p} + \frac{1}{2}\rho v_{p}^{2}$$

Physics 141/151/161

・ロト・4回ト・ミト・ミト・ミー・シック



Choose coordinates like those shown. Evaluate  $P_p = P_a + \rho g D$ . Apply Bernoulli Formula:

$$P_a + \rho g(H + D) + \frac{1}{2}\rho v_b^2 = P_p + \frac{1}{2}\rho v_p^2$$

or (neglecting  $\frac{1}{2}\rho v_b^2$  because  $v_b \ll v_p$  because  $A \gg a$  – Torricelli assumption):

$$\frac{1}{2}\rho v_{\rho}^{2} = P_{a} + \rho g H + \rho g D - P_{a} - \rho g D = \rho g H \Rightarrow \boxed{v_{\rho} = \sqrt{2gH}}$$

cs 141/151/16
## Draining into a Lake-Solution



Choose coordinates like those shown. Evaluate  $P_p = P_a + \rho g D$ . Apply Bernoulli Formula:

$$P_{a} + \rho g(H + D) + \frac{1}{2}\rho v_{b}^{2} = P_{p} + \frac{1}{2}\rho v_{p}^{2}$$

▲□▶▲圖▶▲圖▶▲圖▶ 圖 のへで

or (neglecting  $\frac{1}{2}\rho v_b^2$  because  $v_b \ll v_p$  because  $A \gg a$  – Torricelli assumption):

$$\frac{1}{2}\rho v_{\rho}^{2} = P_{a} + \rho g H + \rho g D - P_{a} - \rho g D = \rho g H \Rightarrow v_{\rho} = \sqrt{2gH}$$

This makes sense! If H = 0, the water will not flow ( $v_p = 0$ ). The contribution to the pressure from the extra depth D basically cancels out.

141/151/16

## Draining into a Lake-Solution



Choose coordinates like those shown. Evaluate  $P_p = P_a + \rho g D$ . Apply Bernoulli Formula:

$$P_{a} + \rho g(H+D) + \frac{1}{2}\rho v_b^2 = P_p + \frac{1}{2}\rho v_p^2$$

or (neglecting  $\frac{1}{2}\rho v_b^2$  because  $v_b \ll v_p$  because  $A \gg a$  – Torricelli assumption):

$$\frac{1}{2}\rho v_p^2 = P_a + \rho g H + \rho g D - P_a - \rho g D = \rho g H \Rightarrow v_p = \sqrt{2gH}$$

This makes sense! If H = 0, the water will not flow ( $v_p = 0$ ). The contribution to the pressure from the extra depth D basically cancels out.

The flow is then easy:

$$I_p = v_p a = a \sqrt{2gH}$$

where the speed in the pipe is much larger than the speed of water in *either* the rainbarrel *or* the body of the lake.



- A disk of mass *m* and radius *r* is gently set on a rough circular floor so that it makes an angle θ<sub>0</sub> relative to a vertical through the center of curvature of the floor, with its center of mass a distance *R* from the center of curvature as shown, and is released from rest at *t* = 0 so that it *rolls without slipping and oscillates*.
- Find: a)  $\omega$  of the oscillation; b)  $\theta(t)$ ; c)  $f_s(t)$  (the force of static friction as a function of time!).

(ロ)、(型)、(E)、(E)、(E)、(O)、(O)



- A disk of mass *m* and radius *r* is gently set on a rough circular floor so that it makes an angle θ<sub>0</sub> relative to a vertical through the center of curvature of the floor, with its center of mass a distance *R* from the center of curvature as shown, and is released from rest at *t* = 0 so that it *rolls without slipping and oscillates*.
- Find: a)  $\omega$  of the oscillation; b)  $\theta(t)$ ; c)  $f_s(t)$  (the force of static friction as a function of time!).

(ロ)、(型)、(E)、(E)、(E)、(O)、(O)

Draw a force diagram on the rolling mass at a general angle  $\boldsymbol{\theta}.$ 



- A disk of mass *m* and radius *r* is gently set on a rough circular floor so that it makes an angle  $\theta_0$  relative to a vertical through the center of curvature of the floor, with its center of mass a distance *R* from the center of curvature as shown, and is released from rest at t = 0 so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) θ(t); c)
   f<sub>s</sub>(t) (the force of static friction as a function of time!).

< (17) >

4 ∃ →

ъ

Draw a force diagram on the rolling mass at a general angle  $\theta$ . Choose a positive direction for  $\theta$  and (I recommend) choose to use  $s = R\theta$  as a linear coordinate and choose a pivot either at the CM of the disk or the point where it touches the floor.



- A disk of mass *m* and radius *r* is gently set on a rough circular floor so that it makes an angle  $\theta_0$  relative to a vertical through the center of curvature of the floor, with its center of mass a distance *R* from the center of curvature as shown, and is released from rest at t = 0 so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) θ(t); c)
   f<sub>s</sub>(t) (the force of static friction as a function of time!).

< (C) >

⇒

ъ

Draw a force diagram on the rolling mass at a general angle  $\theta$ . Choose a positive direction for  $\theta$  and (I recommend) choose to use  $s = R\theta$  as a linear coordinate and choose a pivot either at the CM of the disk or the point where it touches the floor. Write N2 for both torque and force.



- A disk of mass *m* and radius *r* is gently set on a rough circular floor so that it makes an angle  $\theta_0$  relative to a vertical through the center of curvature of the floor, with its center of mass a distance *R* from the center of curvature as shown, and is released from rest at t = 0 so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) θ(t); c)
   f<sub>s</sub>(t) (the force of static friction as a function of time!).

Draw a force diagram on the rolling mass at a general angle  $\theta$ . Choose a positive direction for  $\theta$  and (I recommend) choose to use  $s = R\theta$  as a linear coordinate and choose a pivot either at the CM of the disk or the point where it touches the floor. Write N2 for both torque and force. Rearrange into SHOE, find  $\omega$ , write  $\theta(t) = s/R$ , and backsubstitute to find  $f_s$ .



- A disk of mass m and radius r is gently set on a rough circular floor so that it makes an angle  $\theta_0$  relative to a vertical through the center of curvature of the floor, with its center of mass a distance R from the center of curvature as shown, and is released from rest at t = 0 so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) θ(t); c)
   f<sub>s</sub>(t) (the force of static friction as a function of time!).

< 3 b

ъ

Draw a force diagram on the rolling mass at a general angle  $\theta$ . Choose a positive direction for  $\theta$  and (I recommend) choose to use  $s = R\theta$  as a linear coordinate and choose a pivot either at the CM of the disk or the point where it touches the floor. Write N2 for both torque and force. Rearrange into SHOE, find  $\omega$ , write  $\theta(t) = s/R$ , and backsubstitute to find  $f_s$ .



s 141/151/16

pivot  

$$R$$
  
 $\theta$   
 $R$   
 $R$   
 $\theta$   
 $R$   
 $r_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$   
We write N2 for translation:  
 $f_s - mg\sin\theta = a_t$ 

Physics 141/151/161



We'll make  $\theta$  positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

 $f_s - mg\sin\theta = a_t$ 

The rolling constraint is tricky. It involves *little r* and the angle  $\phi$  through which the disk rotates, and when  $v_t$  is positive,  $\Omega_{\rm disk} = \frac{d\phi}{dt}$  is *negative* (out of the page), so:  $v_t = -r\Omega_{\rm disk}$ ,  $a_t = -r\alpha_{\rm disk}$ 



We'll make  $\theta$  positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

 $f_s - mg\sin\theta = a_t$ 

The rolling constraint is tricky. It involves *little r* and the angle  $\phi$  through which the disk rotates, and when  $v_t$  is positive,  $\Omega_{\rm disk} = \frac{d\phi}{dt}$  is *negative* (out of the page), so:  $v_t = -r\Omega_{\rm disk}$ ,  $a_t = -r\alpha_{\rm disk}$ 

< (5<sup>1</sup>) ►

Using this, we write N2 for rotation using the CM of the disk as pivot:

 $rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t.$ 



+ |- : -

We'll make  $\theta$  positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R \frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R \frac{d^2\theta}{dt^2}$$

We write N2 for translation:

 $f_s - mg\sin\theta = a_t$ 

The rolling constraint is tricky. It involves *little r* and the angle  $\phi$  through which the disk rotates, and when  $v_t$  is positive,  $\Omega_{disk} = \frac{d\phi}{dt}$  is *negative* (out of the page), so:  $v_t = -r\Omega_{disk}$ ,  $a_t = -r\alpha_{disk}$ 

$$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t$$
. Subtract the two N2s:  $-mg\sin\theta = \frac{3}{2}mR\frac{d^2\theta}{dt^2}$ ,



We'll make  $\theta$  positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R \frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R \frac{d^2\theta}{dt^2}$$

We write N2 for translation:

 $f_s - mg\sin\theta = a_t$ 

The rolling constraint is tricky. It involves *little r* and the angle  $\phi$  through which the disk rotates, and when  $v_t$  is positive,  $\Omega_{\text{disk}} = \frac{d\phi}{dt}$  is *negative* (out of the page), so:  $v_t = -r\Omega_{\text{disk}}$ ,  $a_t = -r\alpha_{\text{disk}}$ 

< (17) >

▲ Ξ ► ▲ Ξ ► Ξ = •○ < ○</p>

$$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t$$
. Subtract the two N2s:  $-mg\sin\theta = \frac{3}{2}mR\frac{d^2\theta}{dt^2}$ ,

make the small angle approximation and rearrange into



We'll make  $\theta$  positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

 $f_s - mg\sin\theta = a_t$ 

The rolling constraint is tricky. It involves *little r* and the angle  $\phi$  through which the disk rotates, and when  $v_t$  is positive,  $\Omega_{disk} = \frac{d\phi}{dt}$  is *negative* (out of the page), so:  $v_t = -r\Omega_{disk}$ ,  $a_t = -r\alpha_{disk}$ Using this, we write N2 for rotation using the CM of the disk as pivot:

(ロ)、(型)、(E)、(E)、(E)、(O)、(O)

$$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t$$
. Subtract the two N2s:  $-mg\sin\theta = \frac{3}{2}mR\frac{d^2\theta}{dt^2}$ , make the small angle approximation and rearrange into  $\frac{d^2\theta}{dt^2} + \frac{2g}{3R}\theta = 0$ . Thus:



We'll make  $\theta$  positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

 $f_s - mg\sin\theta = a_t$ 

The rolling constraint is tricky. It involves *little r* and the angle  $\phi$  through which the disk rotates, and when  $v_t$  is positive,  $\Omega_{disk} = \frac{d\phi}{dt}$  is *negative* (out of the page), so:  $v_t = -r\Omega_{disk}$ ,  $a_t = -r\alpha_{disk}$ Using this, we write N2 for rotation using the CM of the disk as pivot:

$$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t$$
. Subtract the two N2s:  $-mg\sin\theta = \frac{3}{2}mR\frac{d^2\theta}{dt^2}$ , make the small angle approximation and rearrange into  $\frac{d^2\theta}{dt^2} + \frac{2g}{3R}\theta = 0$ . Thus:

$$\omega = \sqrt{\frac{2g}{3R}} \qquad \theta(t) = \theta_0 \cos(\sqrt{\frac{2g}{3R}}t) \qquad f_s = -\frac{1}{2}ma_t = \frac{mg}{3}\theta_0 \cos(\sqrt{\frac{2g}{3R}}t)$$

Physics 141/151/161

• Note that  $f_s$  is a function of time!

- Note that  $f_s$  is a function of time!
- Note that f<sub>s</sub> is **not** μ<sub>s</sub>N. Indeed, both μ<sub>s</sub> and N are irrelevant to the solution as long as μ<sub>s</sub>N is large enough throughout that the disk rolls without slipping.

s 141/151/16

◆□▶ ◆□▶ ◆ □▶ ◆ □▶ ● □ ● ○ ○ ○ ○

- Note that  $f_s$  is a function of time!
- Note that f<sub>s</sub> is **not** μ<sub>s</sub>N. Indeed, both μ<sub>s</sub> and N are irrelevant to the solution as long as μ<sub>s</sub>N is large enough throughout that the disk rolls without slipping.
- Note  $f_s$  always has the same sign as  $\theta(t)$  when it is positive (on the left half of the curved floor)  $f_s$  points up the incline, when it is negative (or the right half of the curved floor)  $f_s$  points up the incline, to the right! It is symmetric, as it must be as we could be viewing the solution from the other side of the page!

s 141/151/16

< ロ > < 団 > < 豆 > < 豆 > < 豆 > < 豆 > < 豆 > < < つ < O < O</p>

- Note that *f<sub>s</sub>* is a function of time!
- Note that f<sub>s</sub> is **not** μ<sub>s</sub>N. Indeed, both μ<sub>s</sub> and N are irrelevant to the solution as long as μ<sub>s</sub>N is large enough throughout that the disk rolls without slipping.
- Note  $f_s$  always has the same sign as  $\theta(t)$  when it is positive (on the left half of the curved floor)  $f_s$  points up the incline, when it is negative (or the right half of the curved floor)  $f_s$  points up the incline, to the right! It is symmetric, as it must be as we could be viewing the solution from the other side of the page!
- If we wanted to find the angular velocity of the disk about its own center of mass, from the previous page:

$$-r\Omega_{
m disk} = Rrac{d heta(t)}{dt} \Rightarrow \Omega_{
m disk} = -rac{R}{r}rac{d heta}{dt} = rac{R}{r}\sqrt{rac{2g}{3R}}\sin(\sqrt{rac{2g}{3R}}t)$$

< ロ > < 団 > < 豆 > < 豆 > < 豆 > < 豆 > < 豆 > < < つ < O < O</p>

- Note that *f<sub>s</sub>* is a function of time!
- Note that f<sub>s</sub> is **not** μ<sub>s</sub>N. Indeed, both μ<sub>s</sub> and N are irrelevant to the solution as long as μ<sub>s</sub>N is large enough throughout that the disk rolls without slipping.
- Note  $f_s$  always has the same sign as  $\theta(t)$  when it is positive (on the left half of the curved floor)  $f_s$  points up the incline, when it is negative (or the right half of the curved floor)  $f_s$  points up the incline, to the right! It is symmetric, as it must be as we could be viewing the solution from the other side of the page!
- If we wanted to find the angular velocity of the disk about its own center of mass, from the previous page:

$$-r\Omega_{
m disk} = Rrac{d heta(t)}{dt} \Rightarrow \Omega_{
m disk} = -rac{R}{r}rac{d heta}{dt} = rac{R}{r}\sqrt{rac{2g}{3R}}\sin(\sqrt{rac{2g}{3R}}t)$$

This too makes sense! At t = 0, the disk starts to roll *down to the right*, so  $\Omega_{\rm disk}$  is into the page, positive. You should be able to trace each quarter cycle of its oscillation and see that everything is consistent and correct.

Suppose: Amplitude A = 1 cm; Wavelength  $\lambda = 0.5$  m; Period T = 0.001 sec Write down the formula for a transverse wave travelling *in the* -x *direction* What is the speed of the wave on the string in terms of the givens? Which of the following changes would *double the power* transmitted by the string (changing *only one of* A, T,  $\lambda$  and nothing else)?



- Change the amplitude to  $A' = 0.707 \ A$
- Change the amplitude to A' = 2 A
- Change the period to T' = 0.707 T
- Change the period to T' = 0.5 T
- Change the wavelength to  $\lambda'=$  0.5  $\lambda$

< ロ > < 団 > < 豆 > < 豆 > < 豆 > < 豆 > < 豆 > < < つ < O < O</p>

Change the wavelength to  $\lambda'=$  2.0  $\lambda$ 

Suppose: Amplitude A = 1 cm; Wavelength  $\lambda = 0.5$  m; Period T = 0.001 sec Write down the formula for a transverse wave travelling *in the* -x *direction* What is the speed of the wave on the string in terms of the givens? Which of the following changes would *double the power* transmitted by the string (changing *only one of* A, T,  $\lambda$  and nothing else)?



< ロ > < 団 > < 豆 > < 豆 > < 豆 > < 豆 > < 豆 > < < つ < O < O</p>

Use: 
$$y(x,t) = A\sin(\frac{2\pi}{\lambda}x + \frac{2\pi}{T}t)$$

Suppose: Amplitude A = 1 cm; Wavelength  $\lambda = 0.5$  m; Period T = 0.001 sec Write down the formula for a transverse wave travelling *in the* -x *direction* What is the speed of the wave on the string in terms of the givens? Which of the following changes would *double the power* transmitted by the string (changing *only one of* A, T,  $\lambda$  and nothing else)?

< ロ > < 団 > < 豆 > < 豆 > < 豆 > < 豆 > < 豆 > < < つ < O < O</p>



Use: 
$$y(x, t) = A \sin(\frac{2\pi}{\lambda}x + \frac{2\pi}{T}t)$$
 and  $v = \frac{\lambda}{T}$ 

Suppose: Amplitude A = 1 cm; Wavelength  $\lambda = 0.5$  m; Period T = 0.001 sec Write down the formula for a transverse wave travelling *in the* -x *direction* What is the speed of the wave on the string in terms of the givens? Which of the following changes would *double the power* transmitted by the string (changing *only one of* A, T,  $\lambda$  and nothing else)?



Suppose: Amplitude A = 1 cm; Wavelength  $\lambda = 0.5$  m; Period T = 0.001 sec Write down the formula for a transverse wave travelling in the -x direction What is the speed of the wave on the string in terms of the givens? Which of the following changes would *double the power* transmitted by the string (changing **only one of** A, T,  $\lambda$  and nothing else)?



5 DQC

needed!

Suppose: Amplitude A = 1 cm; Wavelength  $\lambda = 0.5$  m; Period T = 0.001 sec Write down the formula for a transverse wave travelling in the -x direction What is the speed of the wave on the string in terms of the givens? Which of the following changes would *double the power* transmitted by the string (changing only one of A, T,  $\lambda$  and nothing else)?



needed!

\* - The solution is on the next page. Don't advance until you are ready!

# Construct a Travelling Wave-Solution

 $y(x, t) = 0.01 \sin(4\pi x + 2000\pi t) \text{ m}$ 

Robert G B

$$v = \frac{\lambda}{T} = 500 \text{ m/sec}$$

ry Physics 141/151/161

## Construct a Travelling Wave-Solution

 $y(x, t) = 0.01 \sin(4\pi x + 2000\pi t) \text{ m}$ 

$$v = \frac{\lambda}{T} = 500 \text{ m/sec}$$

Start with  $P = \frac{1}{2}\mu\omega^2 A^2 v$ . Then:  $P \propto A^2$ ; also both  $\omega = \frac{2\pi}{T}$  and  $v = \frac{\lambda}{T}$  change, so  $P \propto \frac{1}{T^3}$ ; finally if  $\lambda$  changes only v changes, so  $P \propto \lambda$ . Hence:

Change the amplitude to  $A' = 0.707 \ A \ (No! \ P \propto A^2)$ Change the amplitude to  $A' = 2 \ A \ (No! \ P \propto A^2)$ Change the period to  $T' = 0.707 \ T \ (No! \ P \propto \frac{1}{T^3})$ Change the period to  $T' = 0.5 \ T \ (No! \ P \propto \frac{1}{T^3})$ Change the vavelength to  $\lambda' = 0.5 \ \lambda \ (No! \ P \propto \lambda)$ Change the wavelength to  $\lambda' = 2.0 \ \lambda \ (Yes! \ P \propto \lambda)$ 



You are slowed down, being overtaken by an ambulance that is travelling at twice your speed of  $v_0$ . You happen to know from your days working in EMS that the frequency of the siren of the ambulance is  $f_0$ , but the frequency detector app on your phone reads  $f_1 > f_0$ . Using  $f_0$ ,  $f_1$  and  $v_a$  (the speed of sound in air) find an expression for  $v_0$ , the speed of your car at the time. Evaluate this for  $f_0 = 1900$  Hz,  $f_1 = 2000$  Hz.

э.



You are slowed down, being overtaken by an ambulance that is travelling at twice your speed of  $v_0$ . You happen to know from your days working in EMS that the frequency of the siren of the ambulance is  $f_0$ , but the frequency detector app on your phone reads  $f_1 > f_0$ . Using  $f_0$ ,  $f_1$  and  $v_a$  (the speed of sound in air) find an expression for  $v_0$ , the speed of your car at the time. Evaluate this for  $f_0 = 1900$  Hz,  $f_1 = 2000$  Hz.

э.

Solution Map:



You are slowed down, being overtaken by an ambulance that is travelling at twice your speed of  $v_0$ . You happen to know from your days working in EMS that the frequency of the siren of the ambulance is  $f_0$ , but the frequency detector app on your phone reads  $f_1 > f_0$ . Using  $f_0$ ,  $f_1$  and  $v_a$  (the speed of sound in air) find an expression for  $v_0$ , the speed of your car at the time. Evaluate this for  $f_0 = 1900$  Hz,  $f_1 = 2000$  Hz.

Solution Map: You are a moving receiver, the ambulance is a moving source.



You are slowed down, being overtaken by an ambulance that is travelling at twice your speed of  $v_0$ . You happen to know from your days working in EMS that the frequency of the siren of the ambulance is  $f_0$ , but the frequency detector app on your phone reads  $f_1 > f_0$ . Using  $f_0$ ,  $f_1$  and  $v_a$  (the speed of sound in air) find an expression for  $v_0$ , the speed of your car at the time. Evaluate this for  $f_0 = 1900$  Hz,  $f_1 = 2000$  Hz.

э.

Solution Map:

You are a moving receiver, the ambulance is a moving source. Write down the combined moving source/moving receiver doppler shift formula for  $f_1$ , the double shifted  $f_0$ .



You are slowed down, being overtaken by an ambulance that is travelling at twice your speed of  $v_0$ . You happen to know from your days working in EMS that the frequency of the siren of the ambulance is  $f_0$ , but the frequency detector app on your phone reads  $f_1 > f_0$ . Using  $f_0$ ,  $f_1$  and  $v_a$  (the speed of sound in air) find an expression for  $v_0$ , the speed of your car at the time. Evaluate this for  $f_0 = 1900$  Hz,  $f_1 = 2000$  Hz.

э.

< (5<sup>1</sup>) ►

Solution Map:

You are a moving receiver, the ambulance is a moving source. Write down the combined moving source/moving receiver doppler shift formula for  $f_1$ , the double shifted  $f_0$ . Solve this equation algebraically for  $v_0$  in terms of  $v_a$  (I like to use  $x = v_0/v_a$  in the algebra until the end).



You are slowed down, being overtaken by an ambulance that is travelling at twice your speed of  $v_0$ . You happen to know from your days working in EMS that the frequency of the siren of the ambulance is  $f_0$ , but the frequency detector app on your phone reads  $f_1 > f_0$ . Using  $f_0$ ,  $f_1$  and  $v_a$  (the speed of sound in air) find an expression for  $v_0$ , the speed of your car at the time. Evaluate this for  $f_0 = 1900$  Hz,  $f_1 = 2000$  Hz.

Solution Map:

You are a moving receiver, the ambulance is a moving source. Write down the combined moving source/moving receiver doppler shift formula for  $f_1$ , the double shifted  $f_0$ . Solve this equation algebraically for  $v_0$  in terms of  $v_a$  (I like to use  $x = v_0/v_a$  in the algebra until the end). If you don't remember the doppler shift formula, it is given next. If you do remember it, finish your work before revealing the next step:

 $f' = \frac{1 \pm \frac{v_r}{v_a}}{1 \mp \frac{v_s}{v_a}} f_0$  (upper signs approaching, lower signs receding).



You are slowed down, being overtaken by an ambulance that is travelling at twice your speed of  $v_0$ . You happen to know from your days working in EMS that the frequency of the siren of the ambulance is  $f_0$ , but the frequency detector app on your phone reads  $f_1 > f_0$ . Using  $f_0$ ,  $f_1$  and  $v_a$ (the speed of sound in air) find an expression for  $v_0$ , the speed of your car at the time. Evaluate this for  $f_0 = 1900$  Hz,  $f_1 = 2000$  Hz.

#### Solution Map:

You are a moving receiver, the ambulance is a moving source. Write down the combined moving source/moving receiver doppler shift formula for  $f_1$ , the double shifted  $f_0$ . Solve this equation algebraically for  $v_0$  in terms of  $v_a$  (I like to use  $x = v_0/v_a$  in the algebra until the end). If you don't remember the doppler shift formula, it is given next. If you do remember it, finish your work before revealing the next step:

 $f' = \frac{1 \pm \frac{v_r}{v_s}}{1 \mp \frac{v_s}{v_s}} f_0 \text{ (upper signs approaching, lower signs receding).}$ 

next page. Don't advance


• This one is simple. The car (you, receiver) is receding. The source (ambulance) is approaching. So:

s 141/151



- This one is simple. The car (you, receiver) is receding. The source (ambulance) is approaching. So:
- Let  $x = v_0/v_a$ . Then:

s 141/151

$$f_1 = \frac{1-x}{1-2x} f_0 \Rightarrow (1-2x) f_1 = (1-x) f_0$$



- This one is simple. The car (you, receiver) is receding. The source (ambulance) is approaching. So:
- Let  $x = v_0/v_a$ . Then:

$$f_1 = \frac{1-x}{1-2x} f_0 \Rightarrow (1-2x) f_1 = (1-x) f_0$$

~

• Or:

$$f_1 - f_0 = 2xf_1 - xf_0 = x(2f_1 - f_0) \Rightarrow x = \frac{v_0}{v_a} = \frac{f_1 - f_0}{2f_1 - f_0}$$

cs 141/151/16



- This one is simple. The car (you, receiver) is receding. The source (ambulance) is approaching. So:
- Let  $x = v_0/v_a$ . Then:

$$f_1 = \frac{1-x}{1-2x} f_0 \Rightarrow (1-2x) f_1 = (1-x) f_0$$

• Or:

$$f_1 - f_0 = 2xf_1 - xf_0 = x(2f_1 - f_0) \Rightarrow x = \frac{v_0}{v_a} = \frac{f_1 - f_0}{2f_1 - f_0}$$

• And:

$$v_0 = \frac{f_1 - f_0}{2f_1 - f_0} v_a$$
 or in SI units,  $v_0 = \frac{100}{2100} 343 = \frac{343}{21} \approx 16$  m/sec

If we multiply by 9/4, we get a good estimate of miles per hour:  $v_0 = 37$  mph and the ambulance is going around 75 mph.



In the figure, a neutron star with mass  $M = 10^{30}$  kg and radius R = 8000 m is drawn. Find: a) Escape speed from its surface. First find it algebraically, then evaluate it numerically as a fraction of the speed of light  $c = 3 \times 10^8$  m/sec.

(日本)(日本)(日本)

э.

m/sec. b) A comet of mass  $m = 10^{14}$  kg falls "from infinity" to its surface. Estimate the energy lost to heat in the collision algebraically, and *then* evaluate it numerically, expressing it as a fraction of the relativistic rest energy of the comet.



In the figure, a neutron star with mass  $M = 10^{30}$  kg and radius R = 8000 m is drawn. Find: a) Escape speed from its surface. First find it algebraically, then evaluate it numerically as a fraction of the speed of light  $c = 3 \times 10^8$  m/sec.

b) A comet of mass  $m = 10^{14}$  kg falls "from infinity" to its surface. Estimate the energy lost to heat in the collision algebraically, and *then* evaluate it numerically, expressing it as a fraction of the relativistic rest energy of the comet.

First, use energy conservation to relate total energy at the surface of the comet to total energy at infinity.



In the figure, a neutron star with mass  $M = 10^{30}$  kg and radius R = 8000 m is drawn. Find: a) Escape speed from its surface. First find it algebraically, then evaluate it numerically as a fraction of the speed of light  $c = 3 \times 10^8$  m/sec.

(日)(四)(四)(四)

3

m/sec. b) A comet of mass  $m = 10^{14}$  kg falls "from infinity" to its surface. Estimate the energy lost to heat in the collision algebraically, and *then* evaluate it numerically, expressing it as a fraction of the relativistic rest energy of the comet.

First, use energy conservation to relate total energy at the surface of the comet to total energy at infinity. Remember,  $E_{\infty} = 0$  and then solve for  $v_e$ .



In the figure, a neutron star with mass  $M = 10^{30}$  kg and radius R = 8000 m is drawn. Find: a) Escape speed from its surface. First find it algebraically, then evaluate it numerically as a fraction of the speed of light  $c = 3 \times 10^8$  m/sec.

• = •

э.

b) A comet of mass  $m = 10^{14}$  kg falls "from infinity" to its surface. Estimate the energy lost to heat in the collision algebraically, and *then* evaluate it numerically, expressing it as a fraction of the relativistic rest energy of the comet.

First, use energy conservation to relate total energy at the surface of the comet to total energy at infinity. Remember,  $E_{\infty} = 0$  and then solve for  $v_e$ . Falling in, remember it starts with  $E_{\infty} = 0$  so the total energy at the surface will tell you the kinetic energy at the time of impact.



In the figure, a neutron star with mass  $M = 10^{30}$  kg and radius R = 8000 m is drawn. Find: a) Escape speed from its surface. First find it algebraically, then evaluate it numerically as a fraction of the speed of light  $c = 3 \times 10^8$  m/sec.

< 3 b

ъ

b) A comet of mass  $m = 10^{14}$  kg falls "from infinity" to its surface. Estimate the energy lost to heat in the collision algebraically, and *then* evaluate it numerically, expressing it as a fraction of the relativistic rest energy of the comet.

First, use energy conservation to relate total energy at the surface of the comet to total energy at infinity. Remember,  $E_{\infty} = 0$  and then solve for  $v_e$ . Falling in, remember it starts with  $E_{\infty} = 0$  so the total energy at the surface will tell you the kinetic energy at the time of impact. It's bb with BB fully inelastic so *all* of this KE goes to heat!



In the figure, a neutron star with mass  $M = 10^{30}$  kg and radius R = 8000 m is drawn. Find: a) Escape speed from its surface. First find it algebraically, then evaluate it numerically as a fraction of the speed of light  $c = 3 \times 10^8$  m/sec.

⇒

ъ

b) A comet of mass  $m = 10^{14}$  kg falls "from infinity" to its surface. Estimate the energy lost to heat in the collision algebraically, and *then* evaluate it numerically, expressing it as a fraction of the relativistic rest energy of the comet.

First, use energy conservation to relate total energy at the surface of the comet to total energy at infinity. Remember,  $E_{\infty} = 0$  and then solve for  $v_e$ . Falling in, remember it starts with  $E_{\infty} = 0$  so the total energy at the surface will tell you the kinetic energy at the time of impact. It's bb with BB fully inelastic so *all* of this KE goes to heat!

\* - The solution is on the next page. Don't advance until you are ready!

٩



$$E = 0 = -\frac{GMm}{R} + \frac{1}{2}mv_e^2 \Rightarrow v_e = \sqrt{\frac{2GM}{R}}$$

rv Physics 141/151/161



Robert G. B

• 
$$E = 0 = -\frac{GMm}{R} + \frac{1}{2}mv_e^2 \Rightarrow \boxed{v_e = \sqrt{\frac{2GM}{R}}}$$
  
•  $E = 0 - \frac{GMm}{R} + K \Rightarrow \boxed{K = \Delta E_{heat} = \frac{GMm}{R}}$ 

ory Physics 141/151/161

・ロト・4回ト・4回ト・目・900

• 
$$E = 0 = -\frac{GMm}{R} + \frac{1}{2}mv_e^2 \Rightarrow v_e = \sqrt{\frac{2GM}{R}}$$
  
•  $E = 0 - \frac{GMm}{R} + K \Rightarrow K = \Delta E_{heat} = \frac{GMm}{R}$   
Numerically:  $\frac{v_e}{c} = \frac{1}{c}\sqrt{\frac{2GM}{R}} = \frac{1}{3 \times 10^8}\sqrt{\frac{2 \times 6.67 \times 10^{-11} \times 10^{30}}{8000}} \Rightarrow$ 

cs 141/151/16

・ロト・1日ト・1日ト・1日、 りへぐ

• 
$$E = 0 = -\frac{GMm}{R} + \frac{1}{2}mv_e^2 \Rightarrow v_e = \sqrt{\frac{2GM}{R}}$$
  
•  $E = 0 - \frac{GMm}{R} + K \Rightarrow K = \Delta E_{heat} = \frac{GMm}{R}$   
Numerically:  $\frac{v_e}{c} = \frac{1}{c}\sqrt{\frac{2GM}{R}} = \frac{1}{3 \times 10^8}\sqrt{\frac{2 \times 6.67 \times 10^{-11} \times 10^{30}}{8000}} \Rightarrow$   
 $v_e = 0.43c = 1.3 \times 10^8 \text{ m/sec}$ 

cs 141/151/16

・ロト・1日ト・1日ト・1日、 りへぐ

• 
$$E = 0 = -\frac{GMm}{R} + \frac{1}{2}mv_e^2 \Rightarrow v_e = \sqrt{\frac{2GM}{R}}$$
  
•  $E = 0 - \frac{GMm}{R} + K \Rightarrow K = \Delta E_{heat} = \frac{GMm}{R}$   
Numerically:  $\frac{v_e}{c} = \frac{1}{c}\sqrt{\frac{2GM}{R}} = \frac{1}{3 \times 10^8}\sqrt{\frac{2 \times 6.67 \times 10^{-11} \times 10^{30}}{8000}} \Rightarrow$   
 $v_e = 0.43c = 1.3 \times 10^8 \text{ m/sec}$   
And:  $\frac{\Delta E_{heat}}{mc^2} = \frac{GM}{Rc^2} = \frac{6.67 \times 10^{-11} \times 10^{30}}{8000 \times 9 \times 10^{16}} \Rightarrow$ 

cs 141/151/16

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

• 
$$E = 0 = -\frac{GMm}{R} + \frac{1}{2}mv_e^2 \Rightarrow \boxed{v_e = \sqrt{\frac{2GM}{R}}}$$
  
•  $E = 0 = -\frac{GMm}{R} + K \Rightarrow \boxed{k = \Delta E_{heat} = \frac{GMm}{R}}$   
Numerically:  $\frac{v_e}{c} = \frac{1}{c}\sqrt{\frac{2GM}{R}} = \frac{1}{3 \times 10^8}\sqrt{\frac{2 \times 6.67 \times 10^{-11} \times 10^{30}}{8000}} \Rightarrow$   
 $v_e = 0.43c = 1.3 \times 10^8 \text{ m/sec}}$   
And:  $\frac{\Delta E_{heat}}{mc^2} = \frac{GM}{Rc^2} = \frac{6.67 \times 10^{-11} \times 10^{30}}{8000 \times 9 \times 10^{16}} \Rightarrow$   
 $E_{heat} = .093mc^2 = 8.34 \times 10^{29}$  joules.

cs 141/151/16

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

• 
$$E = 0 = -\frac{GMm}{R} + \frac{1}{2}mv_e^2 \Rightarrow v_e = \sqrt{\frac{2GM}{R}}$$
  
•  $E = 0 - \frac{GMm}{R} + K \Rightarrow K = \Delta E_{heat} = \frac{GMm}{R}$   
Numerically:  $\frac{v_e}{c} = \frac{1}{c}\sqrt{\frac{2GM}{R}} = \frac{1}{3 \times 10^8}\sqrt{\frac{2 \times 6.67 \times 10^{-11} \times 10^{30}}{8000}} \Rightarrow$   
 $v_e = 0.43c = 1.3 \times 10^8 \text{ m/sec}$   
And:  $\frac{\Delta E_{heat}}{mc^2} = \frac{GM}{Rc^2} = \frac{6.67 \times 10^{-11} \times 10^{30}}{8000 \times 9 \times 10^{16}} \Rightarrow$   
 $E_{heat} = .093mc^2 = 8.34 \times 10^{29}$  joules.

This *classical*, *non-relativistic* solution isn't quite right! Because  $v_e$  is so close to the speed of light, to do it correctly we'd have to use relativistic expressions for things like the total energy and kinetic energy. But it does give us a realistic appreciation for the strangeness of things like neutron stars!

# The End

#### Feedback Welcome

Send Comments To: rgb at duke dot edu

ductory Physics 141/151/161

・ロト・(型ト・(川下・)) 「、 (し)