Introductory Physics 141/151/161

Self-Guided Learning Problems

Robert G. Brown
Summer, 2020



Contents

1. Kinematics
   - Two Bumper Cars
   - Two Bumper Cars-Solution
   - 2D Basketball Trajectory
   - 2D Basketball Trajectory-Solution
2. Newton's Laws and Force
   - Firing a Speargun
   - Firing a Speargun-Solution
3. Work and Energy
4. Center of Mass, Momentum, Collisions
5. 1D Rotation
6. Vector Torque, Angular Momentum, and Rotational Collisions
7. Static Equilibrium
   - Carrying A Box Up the Stairs
   - Carrying A Box Up the Stairs-Solution
8. Fluids
9. Oscillations
   - Oscillations: A Rolling Pendulum
   - Oscillations: A Rolling Pendulum
10. Waves on a String

About These Problems

This is an experiment. Beamer allows me to make slides that will successively reveal lines of math-heavy text. This gives me a unique opportunity to build a collection of self-guided learning problems for physics that do what I've fantasized about doing for years now – present a problem, then provide a hint, then another hint, then another (or reveal a step, and then another step) until finally, the entire souution is presented, annotated.

Hopefully these problems will help students everywhere as they struggle to learn physics problems solving techniques and learn to "think like a physicist" as they do so.

To use this resource, pick a problem or topic from the table of contents and go directly to it, or work your way through all the problems systematically. Work on a separate sheet of paper, and when you get stuck, page down through the frames to see (hopefully) where you went wrong.

Remember, the point is to **master these problems**, not just to get through them. Make sure that before you are done, you can do every problem **without looking, without hints, and without remembering the exact solution** but rather, understanding *how* to find it!

Kinematics: Two Bumper Cars



- Two bumper cars are headed straight at one another, one travelling at $2v_0$ to the right, the other at speed v_0 to the left. When they are separated by a distance D, the car on the right slows down with a constant acceleration a_0. Does the right hand car manage to stop before being hit by the left hand car?

Kinematics: Two Bumper Cars



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

- Two bumper cars are headed straight at one another, one travelling at $2v_0$ to the right, the other at speed v_0 to the left. When they are separated by a distance D, the car on the right slows down with a constant acceleration a_0. Does the right hand car manage to stop before being hit by the left hand car?

Kinematics: Two Bumper Cars



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

- Two bumper cars are headed straight at one another, one travelling at $2v_0$ to the right, the other at speed v_0 to the left. When they are separated by a distance D, the car on the right slows down with a constant acceleration a_0. Does the right hand car manage to stop before being hit by the left hand car?

Solve the equations of motion for $x_l(t)$, $v_l(t)$, $x_r(t)$, $v_r(t)$ for the left and right hand cars respectively.

Kinematics: Two Bumper Cars



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

- Two bumper cars are headed straight at one another, one travelling at $2v_0$ to the right, the other at speed v_0 to the left. When they are separated by a distance D, the car on the right slows down with a constant acceleration a_0. Does the right hand car manage to stop before being hit by the left hand car?

Solve the equations of motion for $x_l(t)$, $v_l(t)$, $x_r(t)$, $v_r(t)$ for the left and right hand cars respectively. Find the time the car on the right comes to rest, t_r.

Kinematics: Two Bumper Cars



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

- Two bumper cars are headed straight at one another, one travelling at $2v_0$ to the right, the other at speed v_0 to the left. When they are separated by a distance D, the car on the right slows down with a constant acceleration a_0. Does the right hand car manage to stop before being hit by the left hand car?

Solve the equations of motion for $x_l(t)$, $v_l(t)$, $x_r(t)$, $v_r(t)$ for the left and right hand cars respectively. Find the time the car on the right comes to rest, t_r. Evaluate the positions of both cars at that time.

Kinematics: Two Bumper Cars



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

- Two bumper cars are headed straight at one another, one travelling at $2v_0$ to the right, the other at speed v_0 to the left. When they are separated by a distance D, the car on the right slows down with a constant acceleration a_0. Does the right hand car manage to stop before being hit by the left hand car?

Solve the equations of motion for $x_l(t)$, $v_l(t)$, $x_r(t)$, $v_r(t)$ for the left and right hand cars respectively. Find the time the car on the right comes to rest, t_r. Evaluate the positions of both cars at that time. Have they hit already? If they did hit, could you tell *where* they hit?

Kinematics: Two Bumper Cars



First, choose a 1D coordinate frame such as the one drawn above. What are the initial conditions in this coordinate frame?

- Two bumper cars are headed straight at one another, one travelling at $2v_0$ to the right, the other at speed v_0 to the left. When they are separated by a distance D, the car on the right slows down with a constant acceleration a_0. Does the right hand car manage to stop before being hit by the left hand car?

Solve the equations of motion for $x_l(t)$, $v_l(t)$, $x_r(t)$, $v_r(t)$ for the left and right hand cars respectively. Find the time the car on the right comes to rest, t_r. Evaluate the positions of both cars at that time. Have they hit already? If they did hit, could you tell *where* they hit?

The solution is on the next page. Don't advance until you are ready!

Kinematics: Two Bumper Cars-Solution



Solution: $x_l(t) = 2v_0 t, \quad v_l(t) = 2v_0$

$x_r(t) = D - v_0 t + \frac{1}{2} a_0 t^2, \quad v_r(t) = -v_0 + a_0 t$

Kinematics: Two Bumper Cars-Solution



Solution: $x_l(t) = 2v_0 t, \quad v_l(t) = 2v_0$

$x_r(t) = D - v_0 t + \frac{1}{2} a_0 t^2, \quad v_r(t) = -v_0 + a_0 t$

Find the time: $t_r = \frac{v_0}{a_0}$.

Kinematics: Two Bumper Cars-Solution



Solution: $x_l(t) = 2v_0 t, \quad v_l(t) = 2v_0$

$x_r(t) = D - v_0 t + \frac{1}{2} a_0 t^2, \quad v_r(t) = -v_0 + a_0 t$

Find the time: $t_r = \frac{v_0}{a_0}$. The left hand car is then at $x_l(t_r) = \frac{2v_0^2}{a_0}$ and the right hand car is at $x_r(t_r) = D - \frac{v_0^2}{a_0} + \frac{v_0^2}{2a_0} = D - \frac{v_0^2}{2a_0}$.

Kinematics: Two Bumper Cars-Solution



Solution: $x_l(t) = 2v_0 t, \quad v_l(t) = 2v_0$

$x_r(t) = D - v_0 t + \frac{1}{2} a_0 t^2, \quad v_r(t) = -v_0 + a_0 t$

Find the time: $t_r = \frac{v_0}{a_0}$. The left hand car is then at $x_l(t_r) = \frac{2v_0^2}{a_0}$ and the right hand car is at $x_r(t_r) = D - \frac{v_0^2}{a_0} + \frac{v_0^2}{2a_0} = D - \frac{v_0^2}{2a_0}$. If $D - \frac{v_0^2}{2a_0} < \frac{2v_0^2}{a_0}$ they will collide before the right hand car comes to rest. We can simplify this to:

$$D < \frac{5v_0^2}{2a_0}$$

Kinematics: Two Bumper Cars-Solution



Solution: $x_l(t) = 2v_0 t, \quad v_l(t) = 2v_0$

$x_r(t) = D - v_0 t + \frac{1}{2} a_0 t^2, \quad v_r(t) = -v_0 + a_0 t$

Find the time: $t_r = \frac{v_0}{a_0}$. The left hand car is then at $x_l(t_r) = \frac{2v_0^2}{a_0}$ and the right hand car is at $x_r(t_r) = D - \frac{v_0^2}{a_0} + \frac{v_0^2}{2a_0} = D - \frac{v_0^2}{2a_0}$. If $D - \frac{v_0^2}{2a_0} < \frac{2v_0^2}{a_0}$ they will collide before the right hand car comes to rest. We can simplify this to:

$$D < \frac{5v_0^2}{2a_0}$$

It makes sense – larger D makes it *less* likely to collide, larger a_0 makes it *less* likely they will collide, larger v_0 makes it *more* likely.

Kinematics: Two Bumper Cars-Solution



Solution: $x_l(t) = 2v_0 t, \quad v_l(t) = 2v_0$

$x_r(t) = D - v_0 t + \frac{1}{2} a_0 t^2, \quad v_r(t) = -v_0 + a_0 t$

Find the time: $t_r = \frac{v_0}{a_0}$. The left hand car is then at $x_l(t_r) = \frac{2v_0^2}{a_0}$ and the right hand car is at $x_r(t_r) = D - \frac{v_0^2}{a_0} + \frac{v_0^2}{2a_0} = D - \frac{v_0^2}{2a_0}$. If $D - \frac{v_0^2}{2a_0} < \frac{2v_0^2}{a_0}$ they will collide before the right hand car comes to rest. We can simplify this to:

$$D < \frac{5v_0^2}{2a_0}$$

It makes sense – larger D makes it *less* likely to collide, larger a_0 makes it *less* likely they will collide, larger v_0 makes it *more* likely. Knowing they collide, if we write:

$$x_l(t_c) = 2v_0 t_c = D - v_0 t_c + \frac{1}{2} a_0 t_c^2 = x_r(t_c)$$

would let us find the time of collision and answer other questions about e.g. their relative velocity at that time. This is a simple quadratic equation for t_c.

Kinematics: 2D Basketball Trajectory



- A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find v_0, the **speed** he must release the basketball with (in terms of H, R, g and θ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed v_0 and that the acceleration of the basketball is $\vec{a} = -g\hat{j}$, ignoring drag.

Kinematics: 2D Basketball Trajectory



- A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find v_0, the **speed** he must release the basketball with (in terms of H, R, g and θ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed v_0 and that the acceleration of the basketball is $\vec{\boldsymbol{a}} = -g\hat{\boldsymbol{j}}$, ignoring drag.

Hints: First write down $a_x = 0$, $a_y = -g$ and solve for $x(t)$, $v_x(t)$, $y(t)$ and $v_y(t)$.

Kinematics: 2D Basketball Trajectory



- A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find v_0, the **speed** he must release the basketball with (in terms of H, R, g and θ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed v_0 and that the acceleration of the basketball is $\vec{\boldsymbol{a}} = -g\hat{\boldsymbol{j}}$, ignoring drag.

Hints: First write down $a_x = 0$, $a_y = -g$ and solve for $x(t)$, $v_x(t)$, $y(t)$ and $v_y(t)$. Note that there are really two unknowns – v_0 and t_b, the time the ball reaches the basket.

Kinematics: 2D Basketball Trajectory



- A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find v_0, the **speed** he must release the basketball with (in terms of H, R, g and θ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed v_0 and that the acceleration of the basketball is $\vec{\boldsymbol{a}} = -g\hat{\boldsymbol{j}}$, ignoring drag.

Hints: First write down $a_x = 0$, $a_y = -g$ and solve for $x(t)$, $v_x(t)$, $y(t)$ and $v_y(t)$. Note that there are really two unknowns – v_0 and t_b, the time the ball reaches the basket. In order to go through the basket, $x(t_b) = R$ at the same time that $y(t_b) = -H$.

Kinematics: 2D Basketball Trajectory



- A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find v_0, the **speed** he must release the basketball with (in terms of H, R, g and θ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed v_0 and that the acceleration of the basketball is $\vec{\boldsymbol{a}} = -g\hat{\boldsymbol{j}}$, ignoring drag.

Hints: First write down $a_x = 0$, $a_y = -g$ and solve for $x(t)$, $v_x(t)$, $y(t)$ and $v_y(t)$. Note that there are really two unknowns – v_0 and t_b, the time the ball reaches the basket. In order to go through the basket, $x(t_b) = R$ at the same time that $y(t_b) = -H$. Find t_b in terms of v_0 and the givens from the x equation.

Kinematics: 2D Basketball Trajectory



- A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find v_0, the **speed** he must release the basketball with (in terms of H, R, g and θ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed v_0 and that the acceleration of the basketball is $\vec{\boldsymbol{a}} = -g\hat{\boldsymbol{j}}$, ignoring drag.

Hints: First write down $a_x = 0$, $a_y = -g$ and solve for $x(t)$, $v_x(t)$, $y(t)$ and $v_y(t)$. Note that there are really two unknowns – v_0 and t_b, the time the ball reaches the basket. In order to go through the basket, $x(t_b) = R$ at the same time that $y(t_b) = -H$. Find t_b in terms of v_0 and the givens from the x equation. Substitute it into the $y(t_b)$ equation.

Kinematics: 2D Basketball Trajectory



- A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find v_0, the **speed** he must release the basketball with (in terms of H, R, g and θ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed v_0 and that the acceleration of the basketball is $\vec{\boldsymbol{a}} = -g\hat{\boldsymbol{j}}$, ignoring drag.

Hints: First write down $a_x = 0$, $a_y = -g$ and solve for $x(t)$, $v_x(t)$, $y(t)$ and $v_y(t)$. Note that there are really two unknowns – v_0 and t_b, the time the ball reaches the basket. In order to go through the basket, $x(t_b) = R$ at the same time that $y(t_b) = -H$. Find t_b in terms of v_0 and the givens from the x equation. Substitute it into the $y(t_b)$ equation. Solve for v_0. There is some algebra involved!

Kinematics: 2D Basketball Trajectory



- A basketball player shoots a jump hook at a (horizontal) distance R from the basket, releasing the ball at a height H above the rim as shown. To shoot over his opponent's outstretched arm, he releases the basketball at an angle θ with respect to the horizontal.

Find v_0, the **speed** he must release the basketball with (in terms of H, R, g and θ) for the ball to go through the hoop "perfectly" as shown. Assume that his release is on line and undeflected, at initial speed v_0 and that the acceleration of the basketball is $\vec{\boldsymbol{a}} = -g\hat{\boldsymbol{j}}$, ignoring drag.

Hints: First write down $a_x = 0$, $a_y = -g$ and solve for $x(t)$, $v_x(t)$, $y(t)$ and $v_y(t)$. Note that there are really two unknowns – v_0 and t_b, the time the ball reaches the basket. In order to go through the basket, $x(t_b) = R$ at the same time that $y(t_b) = -H$. Find t_b in terms of v_0 and the givens from the x equation. Substitute it into the $y(t_b)$ equation. Solve for v_0. There is some algebra involved!

The solution is on the next page. Don't advance until you are ready!

Kinematics: 2D Basketball Trajectory-Solution

Initial Conditions:

$$a_x = 0, v_{0x} = v_0 \cos\theta, x_0 = 0 \text{ and } a_y = -g, v_{0y} = v_0 \sin\theta, y_0 = 0$$

Integrate:

$$x(t) = v_0 \cos\theta t \quad v_x(t) = v_0 \cos\theta \quad y(t) = -\frac{1}{2}gt^2 + v_0 \sin\theta t \quad v_y(t) = v_0 \sin\theta - gt$$

Find the **time** t_b that the basketball reaches the horizontal position of the hoop:

$$R = v_0 \cos\theta t_b \Rightarrow t_b = R/(v_0 \cos\theta)$$

This must also be the time that the ball has exactly the height of the hoop:

$$-H = -\frac{1}{2}gt_b^2 + v_0 \sin\theta t_b \Rightarrow \frac{gR^2}{2v_0^2 \cos^2\theta} = R\tan\theta + H$$

And finally, we solve for v_0:

$$\boxed{v_0 = \sqrt{\frac{gR^2}{2(R\sin\theta\cos\theta + H\cos^2\theta)}}}$$

After doing the algebra, check the dimensions. Are they OK?

Firing a Speargun

- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:

Firing a Speargun



- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:
First, draw a picture of the *general* motion and drag force.

Firing a Speargun



- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:
First, draw a picture of the *general* motion and drag force. Then, write *Newton's Second Law*, expressing a in terms of v, not x.

Firing a Speargun



- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:
First, draw a picture of the *general* motion and drag force. Then, write *Newton's Second Law*, expressing a in terms of v, not x. Then, integrate to find $v(t)$! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Firing a Speargun



- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:
First, draw a picture of the *general* motion and drag force. Then, write *Newton's Second Law*, expressing a in terms of v, not x. Then, integrate to find $v(t)$! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and $v = \frac{dx}{dt}$!

Firing a Speargun



- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:
First, draw a picture of the *general* motion and drag force. Then, write *Newton's Second Law*, expressing a in terms of v, not x. Then, integrate to find $v(t)$! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and $v = \frac{dx}{dt}$! It will come to rest "at" $t \to \infty$.

Firing a Speargun



- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:
First, draw a picture of the *general* motion and drag force. Then, write *Newton's Second Law*, expressing a in terms of v, not x. Then, integrate to find $v(t)$! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and $v = \frac{dx}{dt}$! It will come to rest "at" $t \to \infty$. So, the range should be the integral of the velocity from 0 to infinity!

Firing a Speargun



- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:
First, draw a picture of the *general* motion and drag force. Then, write *Newton's Second Law*, expressing a in terms of v, not x. Then, integrate to find $v(t)$! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and $v = \frac{dx}{dt}$! It will come to rest "at" $t \to \infty$. So, the range should be the integral of the velocity from 0 to infinity!

Note that it will come *almost* to rest (and in the real world, completely to rest) long before t equals "infinity". Note also that the "terminal velocity" in this problem is *zero* as drag is the only force acting.

Firing a Speargun



- An underwater fisherman fires her speargun at a distant fish. The neutral-buoyancy spear leaves the gun at initial speed v_0 and experiences a *linear* drag force $F_d = -bv$ opposite to its velocity. Find $v(t)$ and R, the maximum range of the spear.

Hints:
First, draw a picture of the *general* motion and drag force. Then, write *Newton's Second Law*, expressing a in terms of v, not x. Then, integrate to find $v(t)$! This involves separating variables and integrating both sides separately, using (easiest) *definite* integrals.

Finding the range is trickier. If you did/do things right, the velocity is decaying exponentially, and $v = \frac{dx}{dt}$! It will come to rest "at" $t \to \infty$. So, the range should be the integral of the velocity from 0 to infinity!

Note that it will come *almost* to rest (and in the real world, completely to rest) long before t equals "infinity". Note also that the "terminal velocity" in this problem is *zero* as drag is the only force acting.

The solution is on the next page. Don't advance until you are ready!

Firing a Speargun-Solution



Firing a Speargun-Solution



$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$

Firing a Speargun-Solution



$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$

$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$

Firing a Speargun-Solution



$$F = -bv = m\frac{dv}{dt} = ma \Rightarrow \frac{dv}{v} = -\frac{b}{m}dt$$

$$\Rightarrow \int_{v_0}^{v(t)} \frac{dv}{v} = \int_0^t -\frac{b}{m}dt$$

$$\Rightarrow \ln\left(\frac{v}{v_0}\right) = -\frac{b}{m}t \Rightarrow e^{\left\{\ln\left(\frac{v}{v_0}\right)=-\frac{b}{m}t\right\}} \Rightarrow \frac{v}{v_0} = e^{-\frac{b}{m}t} \Rightarrow \boxed{v(t) = v_0 e^{-\frac{b}{m}t}}$$

$$\frac{dx}{dt} = v_0 e^{-\frac{b}{m}t} \Rightarrow x(t) = \int_0^x dx = \int_0^t v_0 e^{-\frac{b}{m}t} dt = -\frac{mv_0}{b}\int_0^t e^{-\frac{b}{m}t}\left(-\frac{b}{m}\right)dt$$

$$x(t) = \frac{mv_0}{b}\int_{-bt/m}^{0} e^u du = \frac{mv_0}{b}\left(1 - e^{-\frac{b}{m}t}\right)$$

so the range R is:

$$\boxed{R = x(t \to \infty) = \frac{mv_0}{b}}$$

Static Equilibrium: Carrying A Box Up the Stairs



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?

Static Equilibrium: Carrying A Box Up the Stairs



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing $\phi = \tan^{-1}(h/w)$ in the trig!

Static Equilibrium: Carrying A Box Up the Stairs



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing $\phi = \tan^{-1}(h/w)$ in the trig!

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure.

Static Equilibrium: Carrying A Box Up the Stairs



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing $\phi = \tan^{-1}(h/w)$ in the trig!

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using θ only (not ϕ!).

Static Equilibrium: Carrying A Box Up the Stairs



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing $\phi = \tan^{-1}(h/w)$ in the trig!

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using θ only (not ϕ!). Can you now write down equations for force balance and torque balance?

Static Equilibrium: Carrying A Box Up the Stairs



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing $\phi = \tan^{-1}(h/w)$ in the trig!

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using θ only (not ϕ!). Can you now write down equations for force balance and torque balance? Can you solve the torque balance equation for F_2?

Static Equilibrium: Carrying A Box Up the Stairs



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing $\phi = \tan^{-1}(h/w)$ in the trig!

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using θ only (not ϕ!). Can you now write down equations for force balance and torque balance? Can you solve the torque balance equation for F_2? Can you back substitute to find F_1?

Static Equilibrium: Carrying A Box Up the Stairs



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- First, choose a good pivot and coordinate frame for the torque! Avoid the frame needing $\phi = \tan^{-1}(h/w)$ in the trig!

An optimal choice of frame uses the vertical direction for force balance and the *tipped* frame shown for evaluating the torque. I've provided some useful angles in the figure. For the torque, first decompose the forces in the tipped frame using θ only (not ϕ!). Can you now write down equations for force balance and torque balance? Can you solve the torque balance equation for F_2? Can you back substitute to find F_1?

The solution is on the next page. Don't advance until you are ready!

Static Equilibrium: Carrying A Box Up the Stairs-Solution



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?

Static Equilibrium: Carrying A Box Up the Stairs-Solution



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- $F_{2x} = F_2 \sin\theta$, $F_{2y} = F_2 \cos\theta$, $F_{gx} = -mg \sin\theta$, $F_{gy} = -mg \cos\theta$.

Static Equilibrium: Carrying A Box Up the Stairs-Solution



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- $F_{2x} = F_2 \sin\theta$, $F_{2y} = F_2 \cos\theta$, $F_{gx} = -mg \sin\theta$, $F_{gy} = -mg \cos\theta$.
- (Vertically) $F_1 + F_2 - mg = 0$

Static Equilibrium: Carrying A Box Up the Stairs-Solution



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- $F_{2x} = F_2 \sin\theta$, $F_{2y} = F_2 \cos\theta$, $F_{gx} = -mg \sin\theta$, $F_{gy} = -mg \cos\theta$.
- (Vertically) $F_1 + F_2 - mg = 0$
- $\tau_z = wF_2 \cos\theta - \frac{mg}{2}(w \cos\theta - h \sin\theta) = 0$

Static Equilibrium: Carrying A Box Up the Stairs-Solution



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- $F_{2x} = F_2 \sin\theta$, $F_{2y} = F_2 \cos\theta$, $F_{gx} = -mg \sin\theta$, $F_{gy} = -mg \cos\theta$.
- (Vertically) $F_1 + F_2 - mg = 0$
- $\tau_z = wF_2 \cos\theta - \frac{mg}{2}(w\cos\theta - h\sin\theta) = 0$

So:

$$\boxed{F_2 = \frac{mg}{2}\left(1 - \frac{h}{w}\tan\theta\right)} \text{ and } \boxed{F_1 = \frac{mg}{2}\left(1 + \frac{h}{w}\tan\theta\right)}$$

Static Equilibrium: Carrying A Box Up the Stairs-Solution



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- $F_{2x} = F_2 \sin\theta$, $F_{2y} = F_2 \cos\theta$, $F_{gx} = -mg \sin\theta$, $F_{gy} = -mg \cos\theta$.
- (Vertically) $F_1 + F_2 - mg = 0$
- $\tau_z = wF_2 \cos\theta - \frac{mg}{2}(w\cos\theta - h\sin\theta) = 0$

So:

$$\boxed{F_2 = \frac{mg}{2}\left(1 - \frac{h}{w}\tan\theta\right)} \text{ and } \boxed{F_1 = \frac{mg}{2}\left(1 + \frac{h}{w}\tan\theta\right)}$$

Note: $F_1 > F_2$ for all $\theta \in (0, \pi/2)$. It's better to be the student at the top!

Static Equilibrium: Carrying A Box Up the Stairs-Solution



- Two students are carrying a heavy box of mass m, width w, and height h up the stairs (with center of mass in the middle). The stairs make an angle θ. How is the weight distributed between the two workers?
- $F_{2x} = F_2 \sin\theta$, $F_{2y} = F_2 \cos\theta$, $F_{gx} = -mg \sin\theta$, $F_{gy} = -mg \cos\theta$.
- (Vertically) $F_1 + F_2 - mg = 0$
- $\tau_z = wF_2 \cos\theta - \frac{mg}{2}(w\cos\theta - h\sin\theta) = 0$

So:

$$\boxed{F_2 = \frac{mg}{2}\left(1 - \frac{h}{w}\tan\theta\right)} \text{ and } \boxed{F_1 = \frac{mg}{2}\left(1 + \frac{h}{w}\tan\theta\right)}$$

Note: $F_1 > F_2$ for all $\theta \in (0, \pi/2)$. It's better to be the student at the top! Note: $F_1 = mg$ when $\theta = \tan^{-1}\frac{w}{h}$. At this point $F_2 = 0$ and the student at the top is just helping balance the load!

Oscillations: A Rolling Pendulum



- A disk of mass m and radius r is gently set on a rough circular floor so that it makes an angle θ_0 relative to a vertical through the center of curvature of the floor, with its center of mass a distance R from the center of curvature as shown, and is released from rest at $t = 0$ so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) $\theta(t)$; c) $f_s(t)$ (the force of static friction *as a function of time!*).

Oscillations: A Rolling Pendulum



- A disk of mass m and radius r is gently set on a rough circular floor so that it makes an angle θ_0 relative to a vertical through the center of curvature of the floor, with its center of mass a distance R from the center of curvature as shown, and is released from rest at $t = 0$ so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) $\theta(t)$; c) $f_s(t)$ (the force of static friction *as a function of time!*).

Draw a force diagram on the rolling mass at a general angle θ.

Oscillations: A Rolling Pendulum



- A disk of mass m and radius r is gently set on a rough circular floor so that it makes an angle θ_0 relative to a vertical through the center of curvature of the floor, with its center of mass a distance R from the center of curvature as shown, and is released from rest at $t = 0$ so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) $\theta(t)$; c) $f_s(t)$ (the force of static friction *as a function of time!*).

Draw a force diagram on the rolling mass at a general angle θ. Choose a positive direction for θ and (I recommend) choose to use $s = R\theta$ as a linear coordinate and choose a pivot either at the CM of the disk or the point where it touches the floor.

Oscillations: A Rolling Pendulum



- A disk of mass m and radius r is gently set on a rough circular floor so that it makes an angle θ_0 relative to a vertical through the center of curvature of the floor, with its center of mass a distance R from the center of curvature as shown, and is released from rest at $t = 0$ so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) $\theta(t)$; c) $f_s(t)$ (the force of static friction *as a function of time!*).

Draw a force diagram on the rolling mass at a general angle θ. Choose a positive direction for θ and (I recommend) choose to use $s = R\theta$ as a linear coordinate and choose a pivot either at the CM of the disk or the point where it touches the floor. Write N2 for both torque and force.

Oscillations: A Rolling Pendulum



- A disk of mass m and radius r is gently set on a rough circular floor so that it makes an angle θ_0 relative to a vertical through the center of curvature of the floor, with its center of mass a distance R from the center of curvature as shown, and is released from rest at $t = 0$ so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) $\theta(t)$; c) $f_s(t)$ (the force of static friction *as a function of time!*).

Draw a force diagram on the rolling mass at a general angle θ. Choose a positive direction for θ and (I recommend) choose to use $s = R\theta$ as a linear coordinate and choose a pivot either at the CM of the disk or the point where it touches the floor. Write N2 for both torque and force. Rearrange into SHOE, find ω, write $\theta(t) = s/R$, and backsubstitute to find f_s.

Oscillations: A Rolling Pendulum



- A disk of mass m and radius r is gently set on a rough circular floor so that it makes an angle θ_0 relative to a vertical through the center of curvature of the floor, with its center of mass a distance R from the center of curvature as shown, and is released from rest at $t = 0$ so that it **rolls without slipping and oscillates**.
- Find: a) ω of the oscillation; b) $\theta(t)$; c) $f_s(t)$ (the force of static friction *as a function of time!*).

Draw a force diagram on the rolling mass at a general angle θ. Choose a positive direction for θ and (I recommend) choose to use $s = R\theta$ as a linear coordinate and choose a pivot either at the CM of the disk or the point where it touches the floor. Write N2 for both torque and force. Rearrange into SHOE, find ω, write $\theta(t) = s/R$, and backsubstitute to find f_s.

* - The solution is on the next page. Don't advance until you are ready!

Oscillations: A Rolling Pendulum-Solution



We'll make θ positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

Oscillations: A Rolling Pendulum-Solution



We'll make θ positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

$$f_s - mg\sin\theta = a_t$$

Oscillations: A Rolling Pendulum-Solution



We'll make θ positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

$$f_s - mg\sin\theta = a_t$$

The rolling constraint is tricky. It involves *little r* and the angle ϕ through which the disk rotates, and when v_t is positive, $\Omega_{\rm disk} = \frac{d\phi}{dt}$ is *negative* (out of the page), so: $v_t = -r\Omega_{\rm disk}$, $a_t = -r\alpha_{\rm disk}$

Oscillations: A Rolling Pendulum-Solution



We'll make θ positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

$$f_s - mg\sin\theta = a_t$$

The rolling constraint is tricky. It involves *little r* and the angle ϕ through which the disk rotates, and when v_t is positive, $\Omega_{\rm disk} = \frac{d\phi}{dt}$ is *negative* (out of the page), so: $v_t = -r\Omega_{\rm disk}$, $a_t = -r\alpha_{\rm disk}$

Using this, we write N2 for rotation using the CM of the disk as pivot:

$$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t.$$

Oscillations: A Rolling Pendulum-Solution



We'll make θ positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

$$f_s - mg\sin\theta = a_t$$

The rolling constraint is tricky. It involves *little r* and the angle ϕ through which the disk rotates, and when v_t is positive, $\Omega_{\rm disk} = \frac{d\phi}{dt}$ is *negative* (out of the page), so: $v_t = -r\Omega_{\rm disk}$, $a_t = -r\alpha_{\rm disk}$

Using this, we write N2 for rotation using the CM of the disk as pivot:
$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t$. Subtract the two N2s: $-mg\sin\theta = \frac{3}{2}mR\frac{d^2\theta}{dt^2}$,

Oscillations: A Rolling Pendulum-Solution



We'll make θ positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

$$f_s - mg\sin\theta = a_t$$

The rolling constraint is tricky. It involves *little r* and the angle ϕ through which the disk rotates, and when v_t is positive, $\Omega_{\rm disk} = \frac{d\phi}{dt}$ is *negative* (out of the page), so: $v_t = -r\Omega_{\rm disk}$, $a_t = -r\alpha_{\rm disk}$

Using this, we write N2 for rotation using the CM of the disk as pivot:

$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t$. Subtract the two N2s: $-mg\sin\theta = \frac{3}{2}mR\frac{d^2\theta}{dt^2}$,

make the small angle approximation and rearrange into

Oscillations: A Rolling Pendulum-Solution



We'll make θ positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

$$f_s - mg\sin\theta = a_t$$

The rolling constraint is tricky. It involves *little r* and the angle ϕ through which the disk rotates, and when v_t is positive, $\Omega_{\rm disk} = \frac{d\phi}{dt}$ is *negative* (out of the page), so: $v_t = -r\Omega_{\rm disk}$, $a_t = -r\alpha_{\rm disk}$

Using this, we write N2 for rotation using the CM of the disk as pivot:

$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t$. Subtract the two N2s: $-mg\sin\theta = \frac{3}{2}mR\frac{d^2\theta}{dt^2}$,

make the small angle approximation and rearrange into $\frac{d^2\theta}{dt^2} + \frac{2g}{3R}\theta = 0$. Thus:

Oscillations: A Rolling Pendulum-Solution



We'll make θ positive into the page, s positive to the left. Then:

$$v_t = \frac{ds}{dt} = R\frac{d\theta}{dt}, \quad a_t = \frac{d^2s}{dt^2} = R\frac{d^2\theta}{dt^2}$$

We write N2 for translation:

$$f_s - mg\sin\theta = a_t$$

The rolling constraint is tricky. It involves *little r* and the angle ϕ through which the disk rotates, and when v_t is positive, $\Omega_{\rm disk} = \frac{d\phi}{dt}$ is *negative* (out of the page), so: $v_t = -r\Omega_{\rm disk}$, $a_t = -r\alpha_{\rm disk}$

Using this, we write N2 for rotation using the CM of the disk as pivot:

$rf_s = \frac{1}{2}mr^2\alpha \Rightarrow f_s = -\frac{1}{2}ma_t$. Subtract the two N2s: $-mg\sin\theta = \frac{3}{2}mR\frac{d^2\theta}{dt^2}$,

make the small angle approximation and rearrange into $\frac{d^2\theta}{dt^2} + \frac{2g}{3R}\theta = 0$. Thus:

$$\boxed{\omega = \sqrt{\frac{2g}{3R}}} \qquad \boxed{\theta(t) = \theta_0\cos(\sqrt{\frac{2g}{3R}}t)} \qquad \boxed{f_s = -\frac{1}{2}ma_t = \frac{mg}{3}\theta_0\cos(\sqrt{\frac{2g}{3R}}t)}$$

Oscillations: A Rolling Pendulum-Comments

- Note that f_s is a function of time!

Oscillations: A Rolling Pendulum-Comments

- Note that f_s is a function of time!
- Note that f_s is **not $\mu_s N$**. Indeed, both μ_s and N are irrelevant to the solution as long as $\mu_s N$ is large enough throughout that the disk rolls without slipping.

Oscillations: A Rolling Pendulum-Comments

- Note that f_s is a function of time!
- Note that f_s is **not $\mu_s N$**. Indeed, both μ_s and N are irrelevant to the solution as long as $\mu_s N$ is large enough throughout that the disk rolls without slipping.
- Note f_s always has the same sign as $\theta(t)$ – when it is positive (on the left half of the curved floor) f_s points up the incline, when it is negative (or the right half of the curved floor) f_s points *up the incline, to the right!* It is *symmetric*, as it must be as we could be viewing the solution from the other side of the page!

Oscillations: A Rolling Pendulum-Comments

- Note that f_s is a function of time!
- Note that f_s is **not $\mu_s N$**. Indeed, both μ_s and N are irrelevant to the solution as long as $\mu_s N$ is large enough throughout that the disk rolls without slipping.
- Note f_s always has the same sign as $\theta(t)$ – when it is positive (on the left half of the curved floor) f_s points up the incline, when it is negative (or the right half of the curved floor) f_s points *up the incline, to the right!* It is *symmetric*, as it must be as we could be viewing the solution from the other side of the page!
- If we wanted to find the angular velocity of the disk about its own center of mass, from the previous page:

$$-r\Omega_{\rm disk} = R\frac{d\theta(t)}{dt} \Rightarrow \Omega_{\rm disk} = -\frac{R}{r}\frac{d\theta}{dt} = \frac{R}{r}\sqrt{\frac{2g}{3R}}\sin(\sqrt{\frac{2g}{3R}}t)$$

Oscillations: A Rolling Pendulum-Comments

- Note that f_s is a function of time!
- Note that f_s is **not $\mu_s N$**. Indeed, both μ_s and N are irrelevant to the solution as long as $\mu_s N$ is large enough throughout that the disk rolls without slipping.
- Note f_s always has the same sign as $\theta(t)$ – when it is positive (on the left half of the curved floor) f_s points up the incline, when it is negative (or the right half of the curved floor) f_s points *up the incline, to the right!* It is *symmetric*, as it must be as we could be viewing the solution from the other side of the page!
- If we wanted to find the angular velocity of the disk about its own center of mass, from the previous page:

$$-r\Omega_{\rm disk} = R\frac{d\theta(t)}{dt} \Rightarrow \Omega_{\rm disk} = -\frac{R}{r}\frac{d\theta}{dt} = \frac{R}{r}\sqrt{\frac{2g}{3R}}\sin(\sqrt{\frac{2g}{3R}}t)$$

This too makes sense! At $t = 0$, the disk starts to roll *down to the right*, so $\Omega_{\rm disk}$ is into the page, positive. You should be able to trace each quarter cycle of its oscillation and see that everything is consistent and correct.

The End

Feedback Welcome

Send Comments To: rgb at duke dot edu